

Numerical investigation of dual-stage high velocity oxy-fuel (HVOF) thermal spray process: A study on nozzle geometrical parameters

Jafari, H., Emami, S., & Mahmoudi, Y. (2017). Numerical investigation of dual-stage high velocity oxy-fuel (HVOF) thermal spray process: A study on nozzle geometrical parameters. *Applied Thermal Engineering*, *111*, 745-758. https://doi.org/10.1016/j.applthermaleng.2016.09.145

Published in:

Applied Thermal Engineering

Document Version: Peer reviewed version

Queen's University Belfast - Research Portal: Link to publication record in Queen's University Belfast Research Portal

Publisher rights

© Elsevier Ltd 2017. This manuscript version is made available under the CC-BY-NC-ND 4.0 license http://creativecommons.org/licenses/bync-nd/4.0/ which permits distribution and reproduction for non-commercial purposes, provided the author and source are cited.

General rights

Copyright for the publications made accessible via the Queen's University Belfast Research Portal is retained by the author(s) and / or other copyright owners and it is a condition of accessing these publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy

The Research Portal is Queen's institutional repository that provides access to Queen's research output. Every effort has been made to ensure that content in the Research Portal does not infringe any person's rights, or applicable UK laws. If you discover content in the Research Portal that you believe breaches copyright or violates any law, please contact openaccess@qub.ac.uk.

Open Access

This research has been made openly available by Queen's academics and its Open Research team. We would love to hear how access to this research benefits you. – Share your feedback with us: http://go.qub.ac.uk/oa-feedback

Numerical investigation of dual-stage high velocity oxy-fuel (HVOF) thermal spray process: a study on nozzle geometrical parameters Hamed Jafari¹, Sobhan Emami¹*, Yasser Mahmoudi² ¹ Department of Mechanical Engineering, Najafabad Branch, Islamic Azad University, Najafabad, Iran. ² School of Mechanical and Aerospace Engineering, Queen's University Belfast, Belfast BT9 5AH, UK.

* Correspondence to

Tel.: +98 3142292383; Fax: +98 3142291016; Email: sobhan@pmc.iaun.ac.ir.

9

7

8

10 Abstract

The present study takes the advantage of computational fluid dynamics (CFD) methods to model 11 steady-state, two-dimensional, axisymmetric, turbulent, compressible and combusting flow in a 12 dual-stage high velocity oxy-fuel (HVOF) thermal spray system. The Eulerian method is used to 13 solve the continuum gas phase and the Lagrangian method is utilized for tracking the particles. 14 The effects of particle loads on the continuous gas phase are included in the simulation. Thus, 15 compared to the previous studies, we investigate the influence of coupling between the particle 16 and gas phases in modeling of the dual-stage HVOF process. It is found that decouple modeling 17 of the particle and the continuous phase causes a significant error in velocity of particle at the 18 impact moment, even for low powder particle loading. We further investigate the effects of four 19 geometrical parameters on the behavior of gas phase and consequently the particle phase. Results 20 also show that the turbulent intensity of flow at different sections of the warm spray process is the 21 most important factor determining the radial distribution of nitrogen and temperature in the barrel. 22 It also determines the radial distribution of oxygen in the free jet outside of the barrel. It is further 23 found that reduction of the first nozzle diameter and increasing the length of the divergent section 24 (for a fixed divergent angle) of the convergent-divergent nozzle reduce the particle temperature 25 26 while these changes do not affect the particle velocity. In other words, changing these geometrical parameters has a desirable effect on the particle temperature without causing an undesirable change 27 on the particle velocity. 28

Keywords: thermal spray, dual-stage high velocity oxy-fuel (HVOF), coupled two-phase model,
turbulent mixing, warm spray gun geometry.

31 **1. Introduction**

32 Engineering components are usually exposed to destructive environments, and coating is one of the most common and historical ways for protection of these components. Every component based 33 34 on its mechanical performance and environment properties requires its own coating material and method. From all coating materials, titanium is an excellent coating material for different 35 36 applications including biomedical implants [1, 2], off shore structures [3] and aerospace industry 37 components [4]. The merit of titanium as a coating material nested in its high strength to weight ratio, corrosion resistance, biocompatibility and osseointegrate ability with living organisms [1, 4, 38 5-8]. Thermal spray techniques like high-velocity oxygen-fuel (HVOF) are common to be used 39 for coating different metals. 40

Conventional single-stage HVOF thermal spray systems are typically a high pressure combustion 41 chamber followed by a converging-diverging (C-D) nozzle. Injected particles are accelerated and 42 heated through subsonic and then supersonic combusting gas flow and hit the substrate which is 43 placed at around 300 mm from nozzle exit [9]. In order to form a layer of high quality coating, 44 proper temperature and velocity at the impact moment need to be obtained [9]. HVOF has found 45 to be one of the most efficient techniques to deposit high performance coatings at moderate cost 46 [10]. However, HVOF system has no powerful control over the gas phase temperature and 47 consequently the particle phase temperature. As it can be seen in Fig. 1, the particle temperature 48 in HVOF system is above 900 K and it can go over 2000 K. Furthermore, in HVOF system, 49 50 desirable change in temperature can cause an undesirable change in other characteristics. It is shown by Shamim et al. [11] that a decrease of reactant mass flow rate can cause a tiny desirable 51 reduce in particle temperature but a drastic undesirable decrease in velocity. Moreover, decrease 52 in fuel/oxygen ratio can reduce the temperature, instead produces unburned oxygen and hence 53 increases coating oxide content [11]. 54



55 56

57

Fig. 1. Comparison of particle velocity and temperature in HVOF, cold spray and warm spray thermal spray processes [9] (published with permission).

Therefore, these limitations make single-stage HVOF thermal spray not a suitable coating method 58 for phase-sensitive and temperature sensitive metals like titanium. Melting point of titanium is 59 very low. It also has strong affinity toward oxygen and reacts with oxygen at relatively lower 60 61 temperature compared to other materials [12]. Therefore, it is necessary to keep the temperature of titanium low since its oxidation rate increases exponentially when the particle temperature 62 reaches to about 900 K [13]. Thus, using titanium in single-stage HVOF guns results in very low 63 coating quality with high oxide content. One common titanium coating technique, which can 64 control various detrimental reactions such as oxidation, is cold spray [14, 15]. As it is shown in 65 Fig. 1, particle has low temperature in cold spray, and it hits the substrate while it is in the solid 66 state. This coating system results in low deposition efficiency and high porosities within the 67 coatings [16]. 68

Dual-stage HVOF thermal spray system, which is also called warm spray, is introduced to fill the gap between the cold spray and single-stage HVOF spray processes [9]. Warm spray process inherits particle high momentum from cold spray and high temperature from HVOF spray. Titanium requires both of these characteristics (i.e. high velocity and controlled high temperature) in order to form dense, uniform, low oxide, well adhered and in one word high quality coatings.

Warm spray was first patented by Browning [17] and then developed by many researchers [18-74 21]. The principles of warm spray are similar to HVOF process. As can be seen in Fig. 2, a 75 converging nozzle followed by a mixing chamber is placed between combustion chamber and C-76 D nozzle. In the mixing chamber different mass flow rates of nitrogen are added as coolant in order 77 to dilute the hot gases. This can be known as the powerful temperature regulator in warm spray 78 79 technique. Warm spray gun also has a barrel which joins to the C-D nozzle, and particles are introduced to the flow at the barrel entrance. Based on a study by Kuroda et al. [9], warm spray 80 can maintain particle temperature in the range of 850-1400 K and particle velocity in the range of 81 620-800 m/s. In such a range of velocity, the particle temperature in HVAF (high velocity air fuel) 82 83 gun is between 1100-1300 K. In other words, Kuroda et al. [9] showed that the warm spray provides particle temperature three times wider than HVAF while maintaining the velocity 84 comparable with it. 85



87

Fig. 2. Schematic diagram of a warm spray process.

The processes in the thermal spray guns are very complex and involve multi-phase turbulent flow, 88 chemical reaction, heat transfer and supersonic/subsonic flow transition [22]. Moreover, the 89 influence of processing conditions on particle characteristics and coating quality is highly 90 nonlinear and might not be thoroughly revealed by experimental studies [23]. Hence, numerical 91 techniques are effective tools and can provide an insight into the underlying momentum and heat 92 transfer mechanisms [24, 25]. This further helps to improve the efficiency of HVOF and warm 93 spray coatings by optimizing all of the effective design parameters such as C-D nozzle geometry, 94 fuel/oxygen ratio, particle size and so on [16, 23-31]. 95

While many computational fluid dynamics (CFD) simulations have been done to investigate 96 single-stage HVOF process, researches on the dual-stage HVOF are scarce. Tabbara et al. [3] were 97 pioneered in performing numerical study on the modified HVOF gun. They studied the impact of 98 nitrogen flow rate, nitrogen radial concentration in the barrel and particle trajectory on the particle 99 temperature and velocity. It was concluded that increasing the rate of nitrogen leads to an increase 100 of pressure in the upstream of C-D nozzle, and this intensifies the under-expansion of flow at 101 nozzle outlet. They also found that in the near wall region, where the flow has lower temperature 102 and lower axial velocity, the concentration of the nitrogen is more than central region. Moreover, 103 it was deduced that smaller particles are more likely to get away from the centerline and move to 104 the near wall region. Moreover, the importance of mixing between hot combustion gases and cold 105 nitrogen on the performance of warm spray was emphasized in their paper [3]. Khan and Shamim 106 [16] studied the effects of reactant and coolant mass flow rate and fuel/oxygen ratio on gas and 107

3

particle phases in a warm spray process. They [16] concluded that increasing the reactant mass 108 flow rate increases the particle temperature and velocity. It was further concluded that the highest 109 gas phase temperature occurs at stoichiometric mixture point while particle temperature increases 110 as the fuel/oxygen ratio increases [16]. More coolant flow rate reduces particle temperature and 111 increases the particle velocity only outside of the barrel [16]. Khan and Shamim [30] also 112 investigated the influence of some geometrical parameters in a dual-stage HVOF system and 113 reported that an increase in the combustion chamber diameter or length leads to a decrease in 114 temperature and velocity of particles. They [30] also reported that increasing the length of mixing 115 chamber leads to an increase in the gas phase residence time in the mixing chamber and results in 116 117 better mixing between the hot gases and nitrogen. It causes a significant decrease in the particle temperature. Increase in the diameter of C-D nozzle exit, however, reduces the particle velocity 118 and increases its temperature [30]. 119

The above literature review shows that mixing between hot gases and cold nitrogen is the most 120 sensitive factor and has significant effects on the gas dynamic and thermal behavior of flow in the 121 warm spray and consequently on the particle conditions (i.e. temperature and velocity). Therefore, 122 123 the aim of the present work is studying the nozzle geometry which mostly controls the mixing of hot gases and nitrogen. The paper also visualizes the details of the flow properties in the 124 converging nozzle and C-D nozzle of a dual-stage HVOF. This provides an overview of the 125 sensitivity of the problem upon the geometry of the system. Hence, it highlights the regions in the 126 127 parametric space in which the choice of the nozzle geometry leads to an optimum design of a warm spray. The current paper investigates the influence of four effective geometric parameters of dual-128 stage HVOF gun. These parameters are (i) converging nozzle throat diameter, (ii) C-D nozzle 129 throat diameter, (iii) simultaneous changing of throat diameter of converging nozzle and C-D 130 nozzle and (iv) length of the divergent section of C-D nozzle. In addition, the previous numerical 131 studies considered low particle loading and assumed that the particle phase is decoupled from the 132 gas phase. Thus, another aim of the present work is to investigate the influence of coupling 133 between the particle phase and the gas phases in modeling of a dual-stage HVOF system. The 134 problem includes steady-state, axisymmetric flow calculations for turbulent, fully compressible, 135 high-speed and chemically combusting gas flow. The paper is organized as follows. In section 2 136 we provide the model development and the governing equations. Turbulence and combustion 137 models and the dynamics of the gas and particle phases are introduced in this section. In this 138 section we further give details on the numerical method, computational domain and boundary 139 conditions used to solve the governing equations. Section 3 presents the grid study and verification 140 of the results against previous studies. In section 4 the effect of coupling solution on the particle 141 dynamic is examined. In section 5 the results of the numerical modeling are presented and 142 discussed. In this section the effect of geometrical parameters of the nozzle are studied in detail. 143 144 Finally section 6 concludes the paper.

145 **2. Model development and mathematical formulation**

In the current study, the Eulerian formulation is used to solve the flow field and Lagrangian particle tracking method is utilized to provide particle flow characteristics. The particle phase is coupled with the gas phase, and the impact of particle loads on the gas phase is considered. The gas phase problem contains mass, momentum and energy conservation equations along with turbulence and equilibrium chemistry. The Eulerian method utilizes ideal gas assumption to deal with high speed, 151 compressible and Newtonian flow. Results from gas phase provides Lagrangian scheme with data

to determine particle velocity, temperature and location. Since warm spray gun is completely

153 axisymmetric, a two-dimensional domain is appropriate for computations.

To incorporate the effect of different physical phenomena involve in the problem, we used existing 154 models in the literature. This is mainly due to the complexity of the multi-scale problem involving, 155 compressible turbulent reactive phenomena with heat transfer, and modeling of C-D nozzle in a 156 157 complicated geometry. Interaction between the continuum gas phase by solving Euler equation and tracking particle phase using Lagrangian method, adds more complexity to the problem. 158 Therefore, we tried to utilize previous validated models to develop a validated modeling tool. This 159 further allows us to have a quick model for the purpose of parametric and geometric studies that 160 is the objective of the present work. 161

162 **2.1. Gas phase dynamics**

Viscous, compressible and turbulent flow in a warm spray gun is governed by the compressible reactive Navier–Stokes equations. This consists of balance equations for mass, momentum, energy and species. The ideal gas equation of state couples the pressure and density. The governing equations solved in this study are obtained by Favre (mass-weighted) averaging of transport equations. Therefore, the steady state continuity and momentum equations are written as:

$$\frac{\partial(\bar{\rho}\tilde{u}_j)}{\partial x_j} = 0,\tag{1}$$

$$\frac{\partial(\bar{\rho}\tilde{u}_{j}\tilde{u}_{i})}{\partial x_{j}} = -\frac{\partial\bar{p}}{\partial x_{i}} + \frac{\partial}{\partial x_{j}}\left(\left(\bar{\tau}_{ij}\right)_{eff}\right) + S_{mom,p},\tag{2}$$

$$\left(\bar{\tau}_{ij}\right)_{eff} = \mu_{eff} \left(\frac{\partial \tilde{u}_i}{\partial x_j} + \frac{\partial \tilde{u}_j}{\partial x_i}\right) - \frac{2}{3} \mu_{eff} \frac{\partial \tilde{u}_l}{\partial x_l} \delta_{ij},\tag{3}$$

where ρ is the density of gas, u_j is the *j*th component of the gas field velocity, *p* is the static pressure, and μ_{eff} is the effective viscosity that is considered as the summation of the molecular viscosity, μ , and turbulent eddy viscosity, μ_t . Eddy viscosity is resulted from Reynolds stress terms and represents the effect of diffusing momentum. $(\bar{\tau}_{ij})_{eff}$ and δ_{ij} are the mean deviatoric stress tensor and the Kronecker symbol respectively. The superscripts (~) and (-) denote a massweighted averaged quantity and a Reynolds averaged quantity.

174 In order to simulate two-way coupling, we need to consider the effect of particles on the 175 momentum and energy equations of the continuous phase. Therefore, two terms appear as 176 momentum and energy sinks in the continuous phase equations. For momentum equation (Eq. (2)) 177 the source term $S_{mom,p}$ is calculated as:

$$S_{mom,p} = -\frac{18}{24} \frac{C_D \rho_g}{d_p} \left(\overrightarrow{U_g} - \overrightarrow{U_P} \right) \left| \overrightarrow{U_g} - \overrightarrow{U_P} \right|,\tag{4}$$

where ρ_g and d_p are the density of gas and diameter of particle, respectively. C_D , U_g and U_P are drag coefficient, gas phase velocity and particle phase velocity, respectively

180 The balance equations for energy and species are:

$$\frac{\partial}{\partial x_i} \left[\tilde{u}_i \left(\bar{\rho} \tilde{h}_t + \bar{p} \right) \right] = \frac{\partial}{\partial x_j} \left[\left(\lambda + \frac{c_p \mu_t}{P r_t} \right) \frac{\partial \tilde{T}}{\partial x_j} + \tilde{u}_i \left(\left(\bar{\tau}_{ij} \right)_{eff} \right) - \sum_{k=1}^{N_s} \bar{J}_k \tilde{h}_k \right] + S_{heat,p}, \tag{5}$$

$$\frac{\partial}{\partial x_j} \left(\bar{\rho} \tilde{Y}_k \tilde{u}_j \right) = -\frac{\partial}{\partial x_j} [\bar{J}_k] + \overline{\dot{\omega}}_k; \ k = 1, \cdots, N_s - 1, \tag{6}$$

181 where *T* is the temperature, h_t is the total enthalpy obtained as $h_t = h + u_i u_i/2$, λ is the thermal 182 conductivity, Y_k is mass fraction of the species *k* and $\dot{\omega}_k$ is the mass reaction rate of species per 183 unit volume. \bar{J}_k is the diffusion flux of a species *k* consists of molecular diffusion and effective 184 diffusion due to turbulence. Pr_t is the turbulent Prandtl number that is estimated using Eq. (7) 185 based on the RNG theory [32]:

186
$$\left|\frac{\alpha - 1.3929}{\alpha_0 - 1.3929}\right|^{0.6321} \left|\frac{\alpha + 2.3929}{\alpha_0 + 2.3929}\right|^{0.3679} = \frac{\mu}{\mu_t},$$
 (7)

where μ is the molecular viscosity, μ_t is the turbulent eddy viscosity, $\alpha_0 = 1$, and $\alpha = 1/Pr_t$. The results that obtained from Eq. (7) for Pr_t is in close agreement with experimental data in a variety of flows [32]. This equation has also been used to investigate turbulent reactive flow in the single HVOF and dual stage HVOF (e.g. [16, 22, 26, 28, 30, 31, 43]). For single HVOF, turbulent properties of the flow predicted using Eq. (7), were in good agreement with experimental data [16]. In high Reynolds number, fully developed turbulence flow where μ/μ_t tends to zero, α becomes 1.3929 and the turbulent Prandtl number is $Pr_t = 0.7179$.

194 In Eq. (5) $S_{heat,p}$ is the energy sink in the energy equation of the continuous phase and is calculated 195 by:

196
$$S_{heat,p} = -\rho_P C_P \frac{dT_P}{dt},$$
(8)

where ρ_P , C_p and T_p is density, specific heat at constant pressure and temperature of the particle, respectively.

199 **2.1.1. Turbulence model**

200 In this study the re-normalization group (RNG) k- ε model along with the non-equilibrium wall function treatment is used to predict the turbulent eddy viscosity. Since the nature of the flow in 201 warm spray gun includes complex shear flows [30] with rapid strain and large pressure gradient, 202 203 RNG k- ε is a stronger model in comparison with standard k- ε in order to predict turbulent core of the flow field [33]. This model provides good results for the core flow when the wall y plus is 204 between 30 and 300 [33], which is satisfied in the current simulation. Nonetheless, it cannot solve 205 206 the flow in the boundary layer accurately [33]. However, RNG k- ε is accurate enough to investigate the overall impacts of the geometrical parameters on the flow and particle field. In the RNG k- ε 207 208 turbulence model the turbulent kinetic energy, k, and the rate of turbulent kinetic energy 209 dissipation, ε , are expressed as follows:

$$\frac{\partial(\bar{\rho}\tilde{u}_{j}k)}{\partial x_{j}} = \frac{\partial}{\partial x_{j}} \left[\alpha_{k}(\mu + \mu_{t}) \frac{\partial k}{\partial x_{j}} \right] + G_{k} - \bar{\rho}\varepsilon - Y_{M}, \tag{9}$$

$$\frac{\partial(\bar{\rho}\tilde{u}_{j}\varepsilon)}{\partial x_{j}} = \frac{\partial}{\partial x_{j}} \left[\alpha_{\varepsilon}(\mu + \mu_{t}) \frac{\partial \varepsilon}{\partial x_{j}} \right] + \frac{\varepsilon}{k} (C_{1\varepsilon}G_{k} - \bar{\rho}C_{2\varepsilon}\varepsilon) - R_{\varepsilon}.$$
(10)

210

The constant values of the model in Eqs. (9) and (10) are $C_1 = 1.42$, $C_2 = 1.68$ and $C_{\mu} = 0.084$. α_k

and α_{ε} are the inverse effective Prandtl numbers for k and ε . The production rate of turbulent kinetic

213 energy, G_k , is written as:

214

$$G_k = \mu_t \left(\frac{\partial \tilde{u}_i}{\partial x_j} + \frac{\partial \tilde{u}_j}{\partial x_i} \right) \frac{\partial \tilde{u}_i}{\partial x_j} - \frac{2}{3} \left(\bar{\rho}k + \mu_t \frac{\partial \tilde{u}_l}{\partial x_l} \right) \frac{\partial \tilde{u}_k}{\partial x_k},\tag{11}$$

215 where the turbulent eddy viscosity defined as $\mu_t = \bar{\rho} C_{\mu} k^2 / \epsilon$.

216 **2.1.2. Combustion model**

The eddy dissipation model (EDM) developed by Magnussen and Hjertager [34] is the most 217 common combustion model which is utilized in simulation of HVOF and warm spray guns (e.g. 218 [16, 23, 24, 28, 30, 35, 36]). The EDM is based on the early eddy break-up combustion model 219 220 (EBU) which was introduced by Spalding for the first time [37]. In these models, it is assumed that the reaction rate does not depend on chemical characteristics. As a consequence, the 221 combustion rate is mostly controlled by the turbulent movements of the flow. In other words, 222 223 turbulent flow breaks down eddies with fuel and oxidizer contents, and this process facilitates mixing. In the next step, the reactions are completed at the mixing moment. Therefore, these 224 models are called infinite rate chemistry model or "mixed-is-burnt". Thus, these models are only 225 suitable for problems with high Reynolds and Damkohler numbers (i.e. $Re\rangle$)1 and $Da\rangle$)1) where 226 reaction time scale is much smaller than mixing time scale (which is estimated by k/ε) [38]. 227

In the premixed combustion which happens in the problem of warm spray both fuel and oxygen exist in every single eddy and the minimum dissipation rate of fuel-oxidizer and products will appoint the reaction rate. In EDM, average concentration of species and the turbulent intensity in the flow are the only parameters which determine the reaction rate. Therefore, the volumetric fuel consumption rate is given by:

$$\overline{\dot{\omega}} = -\bar{\rho}A\left(\frac{\varepsilon}{k}\right)\min\left(\tilde{Y}_{F}, \frac{\tilde{Y}_{O}}{S_{O}}, \frac{B\tilde{Y}_{P}}{1+S_{O}}\right),\tag{12}$$

where $S_0 = n_0 M_0 / n_F M_F$. A and B are constants taken as 4 and 0.5, respectively [38].

234 The Eddy Dissipation Model over-predicts the reaction rate in highly strained regions where ε/k ratio is high [38], and this can cause artificial flame to be observed. Moreover, for regions with 235 similar species concentration and turbulence level but different temperatures, this model predicts 236 similar reaction rate. To overcome these shortcomings, new finite rate chemistry combustion 237 models, like eddy dissipation concept (EDC) model [39] and partially stirred reactor (PaSR) model 238 [40] which consider the effects of chemical kinetics, are developed. It is unlikely that the 239 weaknesses of EDM in comparison with the finite rate chemistry models mainly affect the major 240 variables in the flow field and especially particle field. Nonetheless, the absence of a numerical 241 investigation with detailed chemical kinetics in the HVOF system is still conspicuous, and it can 242 be a topic for future researches. 243

Since the effect of chemical kinetics is ignored by EDM, the dissociation of major species should be considered in order to avoid the over-prediction of temperature. When combustion occurs, the gauge pressure and temperature roughly reach to 3.5 bars and 2800 K in the base case (the geometry of the base case is introduced in Fig. 3). In such conditions using an instantaneous equilibrium model leads to the following chemical equation:

 $C_{3}H_{6} + 4.307O_{2} \rightarrow 1.903CO + 1.097CO_{2} + 0.382H + 0.432H_{2} + 2.004H2O + 0.388O + 0.745OH + 0.692O_{2}.$ (13)

The stoichiometric coefficient of each species depends on the combustion chamber pressure and is not known a priori. Li and Christofides [28] used a trial and error method based on a onedimensional (1-D) model along with a chemical equilibrium program (by Gordon and McBride [41]) to calculate the combustion pressure. They [28] showed that for different operating conditions leading to combustion pressures between 3 and 4.8 bars, the difference between calculated pressure from the above mentioned procedure and the experimental data is less than 6%. In this work we used the data presented by Li and Christofides [28] for the chamber pressure.

256 **2.2. Particle phase dynamics**

271

The discrete phase model (DPM) takes the advantage of Lagrangian method to determine the particle motion and temperature using data coming from the gas phase momentum and heat transfer equations. It is assumed in previous studies [3, 11, 16, 27, 30, 42] that since the particle loading in the spray process is very low, the effect of particle dynamics on the continuous phase is minimal. Therefore, the particle phase can be decoupled from the gas phase. However, based on what will be discussed in section 4, decoupling the particle and the continuous phase will cause a remarkable error in prediction of the particle velocity at the impact moment.

It is also assumed that the particles do not affect each other. The particle is considered to be in a spherical shape and their motion is simulated by following equation [33]:

$$m_P \frac{d\overline{V_P}}{dt} = \frac{1}{8} \rho_g A_P C_D \left(\overrightarrow{U_g} - \overrightarrow{U_P} \right) \left| \overrightarrow{U_g} - \overrightarrow{U_P} \right| + \vec{F}, \tag{14}$$

where C_D , U_g and U_P are drag coefficient, gas phase velocity and particle phase velocity, respectively. Also A_p is the surface area of the particle.

While the roughness and orientation of particle surface are important, the particle Reynolds number (Re_p) is the dominant parameter on the drag coefficient [10]. Thus, the following equations define particle drag coefficient and Reynolds number respectively [33].

$$C_D = \begin{cases} \frac{24(1+0.15Re_P^{0.687})}{Re_P}, Re_P \le 10^3\\ 0.44, Re_P > 10^3 \end{cases}.$$
(15)

$$Re_P = \rho_g \frac{|\overrightarrow{U_g} - \overrightarrow{U_P}|}{\mu_g} d_P.$$
(16)

Since the particle Biot number is less than 0.1 [43] the particles internal resistance is ignored and the temperature gradient inside the particle is assumed to be zero. For the base case, we studied the effect of radiation by using the Discrete Ordinate (DO) radiation model. The results predicted for the radiative model are similar to the non-radiative model. Therefore, the effect of radiation is ignored for the rest of the cases studied in this paper. Thus, the heat transfer equation between asingle particle and continues gas phase is described as:

$$m_P C_P \frac{dT_P}{dt} = A_P h_c \big(T_g - T_P \big), \tag{17}$$

where h_c is the convection coefficient obtained as $h_c = Nu\lambda_g/d_P$. Nu is the Nusselt number defined by Ranz and Marshall correlation [44] as $Nu = 2.0 + 0.6Pr^{0.33}Re_d^{0.5}$ and λ_g is the thermal conductivity of the gas phase. Pr also is laminar Prandtl number of the continuous phase defined as $c_p \mu/\lambda_g$.

283 **2.3. Numerical method**

284 We utilized the CFD commercial code ANSYS Fluent 16.1 to solve the governing equations. The 285 solver performs under 2-D, axisymmetric, double precision, steady-state and pressure based 286 conditions. The pressure and density are connected using the ideal gas state equation. Semi-287 Implicit Method for Pressure Linked Equations (SIMPLE) algorithm [45] is employed to treat 288 pressure-velocity coupling. SIMPLE algorithm is commonly used in modeling high speed 289 combusting flow in HVOF guns [16, 26, 30, 35, 36]. Since the radial distribution of nitrogen, 290 oxygen and temperature is studied in this paper, the second order upwind discretization approach 291 is utilized for all equations in order to avoid numerical diffusion.

292 **2.4.** Computational domain and boundary conditions

The schematic diagram and the boundary conditions of a warm spray gun are shown in Fig. 3. The computational domain includes combustion chamber, converging nozzle, mixing chamber, C-D nozzle, barrel and finally atmosphere (where the substrate is located). A, B and C indicate inlets for fuel-oxygen, nitrogen and particle, respectively.



297

282



300 The main objective in the present work is to examine the effect of the nozzle geometry (i.e. 301 converging nozzle and C-D nozzle) on the gas flow and particle behavior in the warm spray. To 302 do this, we consider the change of four effective geometric parameters. These are (i) changing 303 throat diameter of the converging nozzle, (ii) changing the throat diameter of the C-D nozzle, (iii) 304 simultaneous changing of the throat diameter for both converging and C-D nozzles and (iv) length 305 of the C-D nozzle divergent section. This generates 13 geometrical cases which are analyzed 306 numerically in this paper. Table 1 presents the variable dimensions for these 13 cases. Table 2 also 307 presents the working conditions of warm spray. All wall temperatures are fixed at 350 K, and the entrance temperature of fuel-oxygen, nitrogen and particle is assumed to be 300 K [30]. The
ambient pressure is also fixed at 1 atm. The particle diameter is 15 µm and other particle properties
are taken from Ref. [30].

311 312

Table 1. Description of 13 studied cases. The inlet diameter and the divergent angle of the 2nd nozzle are fixed
at 12mm and 1.47°, respectively.

Variable	1 st nozzle	2 nd nozzle	length of the
	throat	throat	2 nd nozzle
case	diameter	diameter	divergent
			portion
Base case	8mm	8mm	40mm
Case 1	6mm		
1 st Group Case 2	7mm	8mm	40mm
Case 3	9mm		
Case 4		6mm	
2 nd Group Case 5	8mm	7mm	40mm
Case 6		9mm	
Case 7	6mm	6mm	
3 rd Group Case 8	7mm	7mm	40mm
Case 9	9mm	9mm	
Case 10			30mm
4 th Group Case 11	8mm	8mm	35mm
Case 12			45mm
Case 13			50mm

313

Table 2.Operating conditions.

parameter	value
Fuel + Oxygen mass flow rate	0.008740 kg/s
Nitrogen mass flow rate	0.008604 kg/s
Particle mass flow rate	0.000668 kg/s

314 3. Grid study and verification of the results

In order to conduct the grid independency test we study the effect of grid resolution on the variation 315 316 of velocity on the centerline. Velocity is an important and sensitive variable in the warm spray gun, and it is important to make sure that this variable is not affected by grid resolution. Hence, 317 three grids with 14100, 54760 (taken from Khan and Shamim [30]) and 129420 cells are used to 318 study the grid independency. Our analysis reveals that grid with 14100 cells provided results with 319 non-physical fluctuations mainly in the barrel. However, results for a grid with 54760 cells are 320 completely logical and the difference between the gas phase velocity for grids with 54760 and 321 129420 cells is less than 3%. It should be mentioned that the percentage of error for the velocity 322 of particle phase is much less than those obtained for the gas phase. Thus, the grid with 54760 323 324 cells is utilized for the rest of the computations.

For validation purposes, the computed temperature and velocity of the particle phase are compared

to those of Khan and Shamim [30]. Fig. 4 depicts a good agreement between the present numericalresults with those of Ref. [30].



Fig. 4. Comparison of (a) temperature and (b) velocity of the particle phase as a function of distance along the centerline obtained in the present work against the numerical results of Ref. [30].

4. Effect of coupled solution on the particle properties

In a study by Yang and Eidelman [42], it is commented that since the particle mass flow rate is 331 less than 4% of continuous phase mass flow rate, the effect of particle loading on the continuous 332 phase is minimal. Therefore, the momentum and heat exchange from particle to the gas phase can 333 be neglected and the particle phase can be decoupled from the gas phase. This approach was used 334 to simulate particle motion and temperature in several numerical investigations of HVOF and 335 warm spray guns (e.g. [3, 11, 16, 27, 30, 42]). To examine this assumption, the current study 336 337 considers the effect of interphase momentum and heat exchange on the particle phase behavior. The results are presented in Figs. 5 and 6. The effect of coupled solution and particle loading on 338 the particle temperature and velocity is shown in Fig. 5. The particles enter the gun at the barrel 339 entrance and path along the centerline until reach to the end of the computational domain. Also, 340 341 Fig. 6 displays the effect of particle loading on the particle temperature and velocity at barrel exit.



Fig. 5. Effect of particle mass flow rate on the particle (a) temperature and (b) velocity.



Fig. 6. Effect of particle mass flow rate on the particle (a) temperature and (b) velocity at barrel exit.

These figures reveal two important facts about the interaction between the two phases. Firstly, Fig. 342 343 6 shows that for percent of particle mass flow rate lower or higher than 3.9%, the velocity and 344 temperature of the particle have a linear dependency to the percent of particle mass flow rate. It seems that the 4% particle loading is not an exact criterion for decoupling particle and gas dynamic. 345 Secondly, as it is seen in Figs. 5 (a) and 6 (a), for a fixed particle mass flow rate (i.e. 3.9%) the 346 particle temperature at barrel exit predicted using decoupled solution is almost 5% lower than that 347 obtained for a coupled solution. Moreover, Figs. 5 (b) and 6 (b) show that at the barrel exit, the 348 particle velocity based on the decoupled solution is almost 10% higher than that of the coupled 349 solution. This further clarifies the role of coupled solution in accurate molding of flow in the warm 350 spray. Thus, in the present work the effect of particle on the continuous phase is considered for all 351 cases studied. 352

353 5. Results and discussion

5.1. Analysis of gas dynamic and particle behavior

Fig. 7 shows the variation of velocity and temperature of the particle and gas phases along the centerline which is obtained for the base case given in Table 1. In warm spray system the combustion chamber temperature increases due to combustion process. This high level of internal energy converts to kinetic energy when the exhaust gases accelerate through a converging nozzle. It can be seen in Fig. 7(a) that the flow experiences 350 m/s increase in velocity when it passes through the converging nozzle. By the next step, nitrogen is added to flow in mixing chamber to cool down the flow. In this stage, velocity and pressure remain roughly constant on the centerline, but the increasing rate of temperature decreases. Then, in C-D nozzle, the flow accelerates and becomes supersonic. Therefore, the flow experiences a drastic decline in pressure and temperature.



Fig. 7. Distribution of (a) velocity and (b) temperature as a function of distance along the centerline obtained for the
base case for gas phase (solid line) and particle phase (dotted line). [a], [b], [c], [d], [e] and [f] indicate combustion
chamber, converging nozzle, mixing chamber, C-D nozzle, barrel and outside atmosphere, respectively.

Fig. 8 presents the contours of velocity and temperature in the computational domain. It is seen when the supersonic flow enters the barrel, it passes through a series of incident and reflected oblique shock waves. This shock structure results in the small fluctuations in velocity and temperature in the barrel as can be seen in Fig. 7. However, both velocity and temperature remains almost constant through the barrel (Fig. 7). When the flow comes out of the barrel, the exhaust
supersonic jet has a boundary surface which interfaces with the surrounding quiescent atmospheric
air [46]. This free boundary reflects an incident shock wave as an expansion wave and vice versa.
Therefore, the diamond-like wave patterns with compression and expansion waves form at
downstream of the barrel exit. This complicated structure causes the gas velocity and temperature
to undergo a series of fluctuations as seen in Fig. 7.

It is further seen in Fig. 7 that the velocity and temperature of the particle phase increase drastically along the centerline up to x = 0.20 m. Then a monotone increase in the particle velocity and temperature are observed up to x = 0.34 m and x = 0.32 m, respectively. It means that the particle obtains its peak temperature and velocity outside of the gun. These maximum values for the base case are 597.5 m/s and 1271.7 K. Then slight decreases in these properties are observed until the exit of the computational domain. After the particle reaches to its peak temperature, the direction of heat transfer changes, and heat transfers from the particle to the gas flow.

From Fig. 7 (a) it is obvious that when the particles are injected to the gun (i.e. barrel entrance),

the gas velocity decreases sharply. This behavior was not observed in the previous simulations of

warm spray process (e.g. [16, 30]). This can be attributed to the interaction between particle and

flow in a two-way coupling manner.



388

Fig. 8. Contour of (a) velocity and (b) temperature of the gas phase for the base case.

389 The following sections discuss the effect of four important geometrical design parameters on the 390 performance of the warm spray guns.

391 **5.2. Effect of converging nozzle throat diameter**

Fig. 9 shows the effect of throat diameter of the converging nozzle on the gas and particle phases' 392 properties. According to Table 1, Case 1 and Case 2 have 1st nozzle throat diameters smaller than 393 the base case while Case 3 has a diameter higher than the base case. Fig. 9 shows that the throat 394 diameter of 1st nozzle does not have significant effect on the flow velocity and temperature 395 upstream of the nozzle while it causes remarkable changes on the flow in the downstream of the 396 nozzle. Up to x = 0.157 m (the barrel entrance), the gas phase velocity is affected by the nozzle 397 throat diameter. Reduction of the first nozzle diameter increases the pressure in the combustion 398 chamber, and reduces the pressure and increases the gas velocity in the mixing chamber. In 399 400 contrast, this change does not affect these variables in the barrel since the stagnation pressure in the mixing chamber is the same for all cases. Therefore, the gas velocity in the barrel does not 401 change with the throat diameter while the gas temperature experiences noticeable changes. Since 402 the flow velocity and pressure at barrel exit are almost equal for all cases, the diamond-like jets at 403 barrel exit, which are visible as fluctuations in Fig. 9, look similar. Fig. 9 shows that increasing 404 the 1st nozzle throat diameter has no remarkable effect on the particle velocity while this change 405 has a substantial effect on the particle temperature. It can be concluded that the behavior of the gas 406 properties have the same effects on the particle properties. It is an interesting finding that changing 407 the diameter of converging nozzle serves a powerful control over the particle temperature while 408 the particle velocity remains intact. Based on the results presented in Fig. 9 (b), 33% decrease in 409 the nozzle throat diameter (comparison between Case 1 and Case 3) causes 11% decline in the 410 particle temperature at the end of the computational domain. The decrease in the gas phase and 411 particle temperature is due to the fact that by reducing the diameter of converging nozzle the 412 turbulent behavior of flow in the mixing chamber and C-D nozzle increases. This enhances the 413 414 turbulent mixing of hot gases and cold nitrogen.

To evaluate of the effect of turbulent mixing, the variation of the turbulent intensity along the centerline is given in Fig. 10 for all above cases. As it is seen, Case 1 (related to minimum nozzle diameter) has the highest level of turbulent intensity in the mixing chamber and C-D nozzle. For this case, the turbulent intensity increases due to a stronger jet-like flow which passes through the converging nozzle resulting in a more strained shear layer. The increase of turbulent intensity enhances the turbulent mixing of hot combustion products and nitrogen cooling gas.

421 To show the effect of turbulent mixing on the radial diffusion of nitrogen, the radial distribution of N₂ mole fraction at the barrel entrance (the location of particle injection) is presented in Fig. 11 422 (a). It is seen that the radial distribution of N_2 in Case 1 is more uniform at barrel entrance. It means 423 that the higher level of turbulent mixing can lead to an increase of radial diffusion of nitrogen. 424 Also, the cooling effect of nitrogen results in a more uniform distribution of radial temperature. 425 The uniform radial distribution of temperature shows its practical importance when the particles 426 get away from the centerline. The radial distance of particle from the centerline determines the 427 degree of heating and melting of the particles. As the particles get away from the centerline, their 428 temperature decreases [3]. In fact, a radial uniformity in gas phase temperature results in an 429 uniformity of the particle temperature regardless of particles' radial distance from the centerline. 430

The effect of throat diameter of the 1^{st} nozzle on the variation of radial O₂ distribution at 63 mm outside of barrel (i.e. x= 320 mm where the particles typically attain their highest temperature) is depicted in Fig. 11 (b). In practice, radial distribution of oxygen determines the oxidant content of

434 particles at the point of impact on the substrate and consequently the coating quality. It can be seen

that the radial O_2 distributions are the same for all cases. The oxygen content of the jet flow in the atmosphere is mostly resulted from jet velocity at barrel exit because the flow with higher velocity at barrel exit faces higher turbulent intensity and higher turbulent mixing with ambient air. Therefore, roughly same velocity at barrel exit (Fig. 9 (a)) leads to the same level of turbulent intensity (Fig. 10) and radial oxygen content (Fig. 11 (b)).



Fig. 9. Effect of throat diameter of the 1st nozzle on the variation of (a) velocities and (b) temperatures of the gas and particle phases along the centerline.



Fig. 10. Effect of throat diameter of the 1st nozzle on the variation of turbulent intensity of flow along the centerline.



Fig. 11. Effect of throat diameter of the 1st nozzle on the variation of (a) nitrogen radial distribution at the barrel entrance and (b) oxygen radial distribution at 63 mm outside of the barrel (i.e. x=320 mm).

440 **5.3. Effect of C-D nozzle throat diameter**

The impact of C-D nozzle throat diameter in a liquid-fueled single stage HVOF gun was studied 441 by Tabbara et al. [44]. The current paper studies the impact of this parameter in a gas-fueled warm 442 spray. Fig. 12 presents the velocity and temperature of gas and particle phases due to a change in 443 the throat diameter of the second nozzle. According to Table 1, Case 4 and Case 5 have 2nd nozzle 444 throat diameters smaller than the base case while Case 6 has a diameter higher than the base case. 445 Changing this parameter does not affect the flow velocity upstream of the throat in the single-stage 446 447 HVOF gun. This was observed in the study by Tabbara et al. [44]. Nonetheless, changing the 2nd 448 nozzle throat diameter has remarkable effect on the upstream velocity of gas, especially in the mixing chamber. As it can be seen in Fig. 12 (a), decrease in C-D nozzle throat diameter results in 449 a reduction of gas velocity in the combustor and mixing chamber. Similar to the single stage, in 450 the dual stage HVOF, a decrease in C-D nozzle throat increases gas velocity and consequently the 451 particle velocity in the downstream of the nozzle throat. An increase of the throat diameter reduces 452 the stagnation pressure in the mixing chamber. Thus, further increase in the throat diameter (i.e. 453 Case 6 in Table 1) causes the flow to expand normally through the nozzle and barrel. This is why 454 no shock structure is seen in Fig. 12 (a) at the barrel exit (dashed green lines in Figs. 12 (a) and 455 (b)). 456

From Fig. 12 (b) it is obvious that by increasing the C-D nozzle diameter, the particle temperature increases from Case 4 to Case 6. The particle temperature is influenced by the gas phase temperature and the residence time of particles in the barrel. Therefore, the increase in the particles temperature from Case 4 to Case 6 is due to both higher gas phase temperature and lower particle velocity (i.e. higher residence time). Based on Fig. 12 (b), 33% decrease in the nozzle throat diameter (going from Case 4 to Case 6) causes 10% decline in the particle temperature and 9% decline in the gas temperature at the end of the computational domain.

Fig. 13 shows the effect of C-D nozzle throat diameter on the turbulent intensity of the flow. As it 464 is mentioned above, the level of turbulent intensity in the mixing chamber and C-D nozzle 465 determines the radial distribution of nitrogen, and consequently, distribution of temperature in the 466 barrel. Compared to the other cases, the turbulent intensity of Case 6 in mixing chamber and C-D 467 nozzle is the highest one. Therefore, in this case the radial distribution of nitrogen (see Fig. 14 (a)), 468 and consequently, the temperature distribution is more uniform. Also the oxygen content of flow 469 outside the barrel is influenced by the turbulent intensity caused by the jet velocity. Therefore, as 470 it is seen in Fig. 14 (b), the highest oxygen content at this region occurs in Case 4 with the highest 471 jet velocity at barrel exit. This increases the peril of oxidation in this case. In a study by Tabbara 472 et al. [44], it was found that 20% reduction in C-D nozzle throat of single stage HVOF resulted in 473 60% increase in the pressure of combustion chamber. The current work shows that 20% decline in 474 C-D nozzle throat causes 65% increase in gauge pressure of the combustion chamber. Hence, the 475 476 impact of C-D nozzle throat diameter on combustion chamber pressure for single and dual HVOF is the same. 477



Fig. 12. Effect of throat diameter of the 2nd nozzle on the variation of (a) velocities and (b) temperatures of the gas and particle phases along the centerline.



Fig. 13. Effect of throat diameter of the 2nd nozzle on the variation of turbulent intensity of flow along the centerline.



Fig. 14. Effect of throat diameter of the 2nd nozzle on the variation of (a) nitrogen radial distribution at the barrel entrance and (b) oxygen radial distribution at 63mm outside of the barrel (i.e. x=320 mm).

5.4. Effect of changing the diameters of both converging and C-D nozzles

The effects of throat diameters of both converging (1^{st}) and C-D (2^{nd}) nozzles on the gas and particle dynamic are studied in this section. Fig. 15 presents the velocity and temperature of gas 481 and particle phases due to a simultaneous change in the 1st and 2nd nozzle throat diameters. 482 According to Table 1, for Case 7 and Case 8 the throat diameters of both nozzles are smaller than 483 the base case while for Case 9 the nozzles have throat diameters higher than the base case. The 484 results presented in this section show that increasing the diameter of the two nozzles to a same 485 level, lessens or intensifies the effect of increasing diameter of each nozzle that we observed in the 486 previous sections.

To explain the effect of this geometric modification on particle velocity, we further inspect Figs. 9 (a), 12 (a) and 15 (a). In Fig. 9 (a), it is seen that an increase in the 1st nozzle throat diameter causes a very slight increase in the velocity (i.e. from 561 m/s to 567 m/s). However, Fig. 12 (a) shows that an increase in the 2nd nozzle throat diameter results in a noticeable decrease in the particle velocity (from 600 m/s to 535 m/s). In Fig. 15 (a) it is seen that simultaneous increase of the 1st and 2nd nozzle throat diameters, decreases the velocity of the particle from 595 m/s to 536 m/s.

The velocity ranges given above show that the decrease in the particle velocity of the third geometrical group (see Table 1) is less severe than the second group. This is because increasing the first nozzle throat diameter has a slight increasing effect on the particle velocity.

This conclusion can also be taken by analyzing the temperature field. Fig. 9 (b) shows that an 497 increase in the converging nozzle throat diameter increases the particle temperature by 135 K. Fig. 498 499 12 (b) also shows that an increase in the C-D nozzle throat diameter increases the particle temperature by 127 K. In Fig. 15 (b) we can see that simultaneous increase in the both nozzle throat 500 diameters increases the particle temperature by 274 K. Thus, it is concluded that simultaneous 501 increase in the both nozzle diameters intensifies separate effects of these changes, and it can 502 503 provide us with the particle temperatures twice wider than the range of particle temperature in the first and second groups of models. 504

Fig. 16 shows the variation of turbulent intensity along the center line due to simultaneous change of diameters for the 1st and 2nd nozzles. It is seen that increasing the diameters of the two nozzles (from Case 7 to Case 9 in Table 1) doesn't noticeably affect the turbulent intensity in the combustion chamber, converging nozzle and mixing chamber (i.e. 0 < x < 0.105 m). On the other hand, in the convergent section of the C-D nozzle the turbulence level is more for Case 7. Therefore, as it can be seen in Fig. 17 (a) the radial distribution of nitrogen and consequently temperature in the barrel is more uniform in Case 7.



Fig. 15. Effect of changing throat diameter of both 1st and 2nd nozzles on the variation of (a) velocities and (b) temperatures of the gas and particle phases along the centerline.



Fig. 16. Effect of changing throat diameter of both 1st and 2nd nozzles on the variation of flow turbulent intensity along the centerline.



Fig. 17. Effect of changing throat diameter of both 1^{st} and 2^{nd} nozzles on the variation of (a) nitrogen radial distribution at barrel entrance and (b) oxygen radial distribution at 63mm outside of the barrel (i.e. x = 320 mm).

Fig. 17 (b) also shows the effects of this geometrical change on the radial distribution of oxygen
outside the barrel. The results of oxygen mole fraction and turbulent mixing outside the barrel
roughly follow what is discussed in the previous parts.

515 **5.5. Effect of the length of divergent section in the C-D nozzle**

516 In this section we study the effect of the length (L) of the divergent section of the C-D nozzle on the velocity, temperature and turbulent intensity of the two phases. With a fixed divergent angel, 517 a longer divergent section of the C-D nozzle gives the gas phase a chance to reach a lower pressure 518 and temperature and consequently higher velocity when it enters the barrel. Fig. 18 shows the 519 variations of the gas and particle velocity and temperature for different lengths of the divergent 520 521 section. For Case 10 which the divergent section length is L = 30 mm, the flow expands normally to around 1 bar through the C-D nozzle and barrel. Thus, no shock wave is observed at the barrel 522 exit. In contrast, in Case 13 with L = 50 mm, the flow over-expands in the C-D nozzle and sharpest 523 series of oblique shocks occur. Fig. 18 (a) shows that while the gas velocity in Case 13 is higher 524

than the other cases, the particle velocity of Case 13 is not more than other cases. The reason is 525 that in this case the flow expands more through a longer divergent section, and the density of the 526 flow and consequently the drag force of the flow acting on the particles decreases. This 527 compensates the effect of higher gas velocity. Fig. 18 (b) shows that as the nozzle length increases, 528 the flow temperature in the C-D nozzle decreases. Therefore, Case 13 in Fig. 18 (b) yields the 529 minimum temperature among different cases. Thus, the gas temperature and consequently the 530 particle temperature is lower than other cases in the barrel. Based on Fig. 18 (b), 40% decrease in 531 L (comparison between Case 10 and Case 13) does not have significant effect on the temperatures 532 of the particle and gas phases at the end of the computational domain. 533

Fig. 19 reveals the turbulent intensity of the flow on the centerline for cases 10 to 13. In Case 13, flow experiences higher speed and stronger shocks at barrel entrance, resulting in more strong stepwise increase in the turbulent intensity and mixing at the barrel entrance. Thus, as it is seen in Fig. 20 (a), the radial distribution of nitrogen at the barrel entrance is more uniform in Case 13. Fig. 20 (b) shows the radial concentration of the oxygen 63 mm outside of the barrel (i.e. x = 320mm in Fig. 3). Roughly same gas phase velocity at the barrel exit leads to same oxygen content at this section.



Fig. 18. Effect of divergent section of the C-D nozzle on the variation of (a) velocities and (b) temperatures of the gas and particle phases along the centerline. For better comparison the places of particle injection in all case are shifted to place of base case injection.



Fig. 19. Effect of divergent section of the C-D nozzle on the variation of turbulent intensity of flow along the centerline.



Fig. 20. Effect of divergent section of the C-D nozzle on the variation of (a) nitrogen radial distribution at the barrel entrance and (b) oxygen radial distribution at 63mm outside of the barrel (i.e. x = 320 mm).

541

542

543 **6. Conclusions**

544 Considering the two-way interaction between gas and particle phases, we conducted a parametric 545 study to investigate the effects of four geometric variables in a dual-stage HVOF thermal spray 546 gun. The emphasis was placed on the effect of the first and second nozzles geometrical parameters 547 on the physical properties such as velocity and temperature of the gas and particle phases. The 548 major findings are as follows:

- Decouple modeling of the particle and the continuous phase causes a significant error in 550 predicting the velocity of particle at the impact moment, even for low particle loads.
- In the first group, decreasing the first nozzle throat diameter results in higher turbulent mixing in the mixing chamber and C-D nozzle. It helps to achieve more uniform radial temperature in the barrel. This change does not affect the particle velocity and decreases the particle temperature. Hence, it can be considered as a way of controlling the particle temperature at a fixed velocity.
- In the second group, decreasing the C-D nozzle throat diameter reduces the particle
 temperature and increases its velocity. Moreover, it increases the oxygen content of the
 free jet outside of barrel and augments the risk of particle oxidation.
- In the third group, when the diameters of both nozzles are changed, the widest variety of
 particle temperature is achieved while the particle velocity remains roughly similar to those
 obtained for the second group.
- By increasing the length of the divergent section of C-D nozzle, the particle velocity does
 not changed. Therefore, this geometrical parameter can be taken as a way of controlling
 particle temperature by preserving its velocity.

565 Funding sources

- This research did not receive any specific grant from funding agencies in the public, commercial,
- or not-for-profit sectors.

568 **Reference**

- 569 [1] D.M. Brunette, P. Tengvall, M. Textor, P. Thomsen. Titanium in Medicine: Material Science,
- 570 Surface Science, Engineering, Biological Responses and Medical Applications, Springer, 2001.
- 571 [2] O.E. Pohler. Unalloyed titanium for implants in bone surgery, Injury, 2000, 31, p. 7–13.

[3] H. Tabbara, S. Gu, D.G. McCartney. Computational modeling of titanium particles in warm
spray, Computers & Fluids, 2011, 44, p. 358-368.

- [4] R.R. Boyer. An overview on the use of titanium in the aerospace industry, Materials Scienceand Engineering: A, 1996, 213, p. 103-114.
- 576 [5] L. Pawlowski. The Science and Engineering of Thermal Spray Coatings, 2nd ed., Wiley, 2008.
- 577 [6] M.J. Donachie. Titanium: a technical guide, 2nd ed., ASM International, 2000.

[7] T. Bernecki. Surface science. In: J.R. Davis, editor. Handbook of Thermal Spray Technology,
 1st print, ASM International, 2004, p. 14-35.

- [8] P.L. Fauchais, J.V.R. Heberlein, M.I. Boulos. Thermal Spray Fundamentals: From Powder to
 Part, 1st print, Springer, 2014.
- 582 [9] S. Kuroda, J. Kawakita, M. Watanabe, K.H. Kim, R. Molak, H. Katanoda. Current Status and
- 583 Future Prospects of Warm Spray Technology. In: N. Espallargas, editor. Future Development of

584 Thermal Spray Coatings: Types, Designs, Manufacture and Applications, 1st ed., Woodhead

585 Publishing, 2015, p. 163-206.

- [10] A. Dolatabadi, J. Mostaghimi, V. Pershin. Effect of a cylindrical shroud on particle conditions
 in high velocity oxy-fuel (HVOF) spray process, Journal of Materials Processing Technology,
 2002, 137, p. 214-224.
- [11] T. Shamim, C. Xia, P. Mohanty. Modeling and analysis of combustion assisted thermal spray
 processes, International Journal of Thermal Sciences, 2007, 46, p. 755-767.
- [12] C. Ponticaud, A. Grimaud, A. Denoirjean, P. Lefort, P. Fauchais. Thermal spray 2001: New
 surfaces for a new millennium, Proceedings of the International Thermal Spray Conferences,
 Singapore, 2001.
- [13] T. Wu, S. Kuroda, J. Kawakitam, H. Katanoda, R. Reed. Processing and properties of titanium
 produced by warm spraying, Proceedings of the 2006 International Thermal Spray Conference,
 Seattle, Washington, USA, 2006.
- [14] M. Watanabe, C. Braunsa, M. Komatsu, S. Kuroda, F. Gärtner, T. Klassen, H. Katanoda.
 Effect of nitrogen flow rate on microstructures and mechanical properties of metallic coatings by
 warm spray deposition, Surface & Coatings Technology, 2013, 232, p. 587-599.

- [15] A. Papyrin, V. Kosarev, S. Klinkov, A. Alkhimov, V.M. Fomin. Cold Spray Technology, 1st
 ed., Elsevier Science, 2007.
- [16] M.N. Khan, T. Shamim. Effect of operating parameters on a dual-stage high velocity oxygen
 fuel thermal spray system, Journal of Thermal Spray Technology, 2014, 23, p. 910-918.
- [17] J. Browning, Thermal spray method and apparatus for optimizing flame jet temperature, USpatent 5330798 A.
- [18] J. Kawakita, S. Kuroda, T. Fukushima, H. Katanoda, K. Matsuo, H. Fukanuma. Dense
 titanium coatings by modified HVOF spraying, Surface & Coatings Technology, 2006, 201, p.
 1250-1255.
- [19] S. Kuroda, J. Kawakita, M. Watanabe, H. Katanoda. Warm spraying-A novel coating process
 based on high-velocity impact of solid particles, Science and Technology of Advanced Materials,
 2008, 9, p. 1-17.
- [20] H. Katanoda, T. Kiriaki, T. Tachibanaki, J. Kawakita, S. Kuroda, M. Fukuhara. Mathematical
 modeling and experimental validation of the warm spray (two-stage HVOF) process, Journal of
 Thermal Spray Technology, 2009, 18, p. 401-410.
- [21] H. Katanoda, H. Morita, M. Komatsu, S. Kuroda. Experimental and numerical evaluation of
 the performance of supersonic two-stage high-velocity oxy-fuel thermal spray (warm spray) gun,
 Journal of Thermal Science, 2011, 20, p. 88-92.
- [22] D. Cheng, Q. Xu, G. Tapaga, E. Lavernia. A numerical study of high-velocity oxygen fuel
 thermal spraying process. Part I: Gas phase dynamics, Metallurgical and Materials Transactions
 A, 2001, 32, p. 1609-1620.
- [23] M. Li and P.D. Christofides. Modeling and control of high-velocity oxygen-fuel (HVOF)
 thermal spray: a tutorial review, Journal of Thermal Spray Technology, 2009, 18, p. 753-768.
- [24] J. Mostaghimi, S. Chandra, R. Ghafouri-Azar, A. Dolatabadi. Modeling thermal spray
 coating processes: A powerful tool in design and optimization, Surface & Coatings Technology,
 2003, 163-164, p. 1-11.
- [25] E. Dongmo, M. Wenzelburger, R. Gadow. Analysis and optimization of the HVOF process
 by combined experimental and numerical approaches, Surface & Coatings Technology, 2008, 202,
 p. 4470-4478.
- [26] J.S Baik, Y.J Kim. Effect of nozzle shape on the performance of high velocity oxygen-fuel
 thermal spray system, Surface & Coatings Technology, 2008, 202, p. 5457-5462.
- [27] M. Li, P.D. Christofides. Modeling and analysis of HVOF thermal spray process accounting
 for powder size distribution, Chemical Engineering Science, 2003, 58, p. 849-857.
- [28] M. Li, P.D. Christofides. Multi-scale modeling and analysis of an industrial HVOF thermal
- 634 spray process, Chemical Engineering Science, 2005, 60, p. 3649-3669.

- [29] M. Li and P.D. Christofides. Feedback control of HVOF thermal spray process accounting
 for Powder size distribution, Journal of Thermal Spray Technology, 2004, 13, p. 108-120.
- [30] M.N. Khan, T. Shamim. Investigation of a dual-stage high velocity oxygen fuel thermal spray
 system, Applied Energy, 2014, 130, p. 853-862.
- [31] M.N. Khan, T. Shamim. Effect of particle and injection parameters on the performance of a
 dual-stage high-velocity oxygen fuel thermal spray system, Journal of Thermal Spray Technology,
- 641 2015, 24, p. 807-816.
- [32] V. Yakhot, S. A. Orszag. Renormalization group analysis of turbulence. I. Basic theory,
 Journal of Scientific Computing, 1986, 1, p. 1-51.
- [33] Fluent 6.3, Users Guide, Fluent Inc., 2006.
- [34] B.F. Magnussen, B.H. Hjertager. On the mathematical modeling of turbulent combustion with
- special emphasis on soot formation and combustion, Proceedings of the Combustion Institute,
- 647 1976, 16, p. 719-729.
- [35] S. Kamnis, S. Gu. 3-D modelling of kerosene-fuelled HVOF thermal spray gun, Chemical
 Engineering Science, 2006, 61, p. 5427-5439.
- [36] S. Kamnis, S. Gu. Numerical modelling of propane combustion in a high velocity oxygen–
 fuel thermal spray gun, Chemical Engineering and Processing, 2006, 45, p. 246–253.
- [37] D.B. Spalding. Mixing and chemical reaction in steady confined turbulent flames,Proceedings of the Combustion Institute, 1971, 13, p. 649-657.
- [38] T. Poinsot, D. Veynante. Theoretical and Numerical Combustion, 2nd ed., R.T. Edwards Inc.,
 2005.
- [39] B.F. Magnussen. On the structure of turbulent and a generalized eddy dissipation concept for
 chemical reaction in turbulent flow, 19th American Institute of Aeronautics and Astronautics
 Aerospace Science Meeting, Missouri, USA, January 12-15, 1981.
- [40] J. Chomiak, A. Karlsson. Flame liftoff in diesel sprays, Proceedings of the CombustionInstitute, 1996, 26, p. 2557-2564.
- [41] S. Gordon, B.J. McBride. Computer program for calculation of complex chemical equilibrium
 compositions and applications, NASA Reference Publication 1311, Cleveland, USA: Lewis
 Research Center, 1994.
- [42] X. Yang, S. Eidelman. Numerical analysis of a high-velocity oxygen-fuel thermal spray
 system, Journal of Thermal Spray Technology, 1996, 5, p. 175-184.
- [43] D. Cheng, Q. Xu, E. Lavernia, G. Tapaga. The effect of particle size and morphology on the
 in-flight behavior of particles during high velocity oxy-fuel thermal spraying, Metallurgical and
 Materials Transactions B, 2001, 32, p. 525-535.

- [44] W.E. Ranz, W.R. Marshall. Evaporation from drops (Part I), Chemical Engineering Progress,
 1952, 48, p. 141-180.
- [45] H.K. Versteeg, W. Malalasekera. An Introduction to Computational Fluid Dynamics, 2nded,
 Prentice Hall, Loughborough, 2007.
- [46] J.D. Anderson. Modern Compressible Flow: with Historical Perspective, 3rd ed., McGraw Hill Education, 2002.
- [47] H. Tabbara, S. Gu. Computational simulation of liquid-fuelled HVOF thermal spraying,
- 676 Surface & Coatings Technology, 2009, 204, p. 676-684.