

Flow patterns and pressure drop of ionic liquid-water two-phase flows in microchannels

Tsaoulidis, D., Dore, V., Angeli, P., Plechkova, N. V., & Seddon, K. R. (2013). Flow patterns and pressure drop of ionic liquid-water two-phase flows in microchannels. *International Journal of Multiphase Flow*, *54*, 1-10. https://doi.org/10.1016/j.ijmultiphaseflow.2013.02.002

Published in:

International Journal of Multiphase Flow

Document Version: Peer reviewed version

Queen's University Belfast - Research Portal: Link to publication record in Queen's University Belfast Research Portal

Publisher rights

This is the author's version of a work that was accepted for publication in International Journal of Multiphase Flow. Changes resulting from the publishing process, such as peer review, editing, corrections, structural formatting, and other quality control mechanisms may not be reflected in this document. Changes may have been made to this work since it was submitted for publication. A definitive version was subsequently published in International Journal of Multiphase Flow, [VOL 54, (2013)]

General rights

Copyright for the publications made accessible via the Queen's University Belfast Research Portal is retained by the author(s) and / or other copyright owners and it is a condition of accessing these publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy

The Research Portal is Queen's institutional repository that provides access to Queen's research output. Every effort has been made to ensure that content in the Research Portal does not infringe any person's rights, or applicable UK laws. If you discover content in the Research Portal that you believe breaches copyright or violates any law, please contact openaccess@qub.ac.uk.

Open Access

This research has been made openly available by Queen's academics and its Open Research team. We would love to hear how access to this research benefits you. – Share your feedback with us: http://go.qub.ac.uk/oa-feedback

Accepted Manuscript

Flow patterns and pressure drop of ionic liquid-water two-phase flows in microchannels

Dimitrios Tsaoulidis, Valentina Dore, Panagiota Angeli, Natalia V. Plechkova, Kenneth R. Seddon

PII:	S0301-9322(13)00032-3
DOI:	http://dx.doi.org/10.1016/j.ijmultiphaseflow.2013.02.002
Reference:	IJMF 1879

To appear in: International Journal of Multiphase Flow

Please cite this article as: Tsaoulidis, D., Dore, V., Angeli, P., Plechkova, N.V., Seddon, K.R., Flow patterns and pressure drop of ionic liquid-water two-phase flows in microchannels, *International Journal of Multiphase Flow* (2013), doi: http://dx.doi.org/10.1016/j.ijmultiphaseflow.2013.02.002

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



Flow patterns and pressure drop of ionic liquid-water two-phase flows in microchannels

Dimitrios Tsaoulidis, Valentina Dore, Panagiota Angeli*

Department of Chemical Engineering, University College London, Torrington Place, WC1E 7JE, UK

Natalia V. Plechkova, Kenneth R. Seddon

QUILL Research centre, School of Chemistry and Chemical Engineering, The Queen's University of Belfast, Belfast BT9 5AG, UK

* Corresponding author: Tel.: ++44 20 7679 3832; Fax: ++44 20 7383 2348; Email: p.angeli@ucl.ac.uk

11

10

3

4 5

6

7

8 9

12 Abstract

13

The two-phase flow of a hydrophobic ionic liquid and water was studied in capillaries made 14 of three different materials (two types of Teflon, FEP and Tefzel, and glass) with sizes 15 between 200 µm and 270 µm. The ionic liquid was 1-butyl-3-methylimidazolium 16 bis{(trifluoromethyl)sulfonyl}amide, with density and viscosity of 1420 kg m⁻³ and 17 0.041 kg m⁻¹ s⁻¹, respectively. Flow patterns and pressure drop were measured for two inlet 18 configurations (T- and Y- junction), for total flow rates of 0.065-214.9 cm³ h⁻¹ and ionic 19 liquid volume fractions from 0.05 to 0.8. The continuous phase in the glass capillary 20 21 depended on the fluid that initially filled the channel. When water was introduced first, it became the continuous phase with the ionic liquid forming plugs or a mixture of plugs and 22 drops within it. In the Teflon microchannels, the order that fluids were introduced did not 23 affect the results and the ionic liquid was always the continuous phase. The main patterns 24 observed were annular, plug, and drop flow. Pressure drop in the Teflon microchannels at a 25 constant ionic liquid flow rate, was found to increase as the ionic liquid volume fraction 26 decreased, and was always higher than the single phase ionic liquid value at the same flow 27 rate as in the two-phase mixture. However, in the glass microchannel during plug flow, 28 pressure drop for a constant ionic liquid flow rate was always lower than the single phase 29 ionic liquid value. A modified plug flow pressure drop model using a correlation for film 30 thickness derived for the current fluids pair showed very good agreement with the 31 experimental data. 32

- 1 Keywords: Micro-fluidics, Liquid-liquid, Pressure drop, Flow patterns, Ionic liquids
- 2

3 **1. Introduction**

4

5 Operations in microchannels have emerged as an important area of research and have found numerous applications in (bio)chemical analysis and synthesis, intensified reactors, 6 7 micropower generation, fuel cells and thermal management systems (Angeli and Gavriilidis, 8 2008). Many of these systems involve two phases, gas-liquid or liquid-liquid. Understanding 9 of the flow characteristics and flow patterns, pressure drop and mass/heat transfer is essential for the design and the precise control of multiphase micro-devices. Although there are many 10 11 studies concerning gas-liquid flows, only limited ones have reported on the flow behaviour of two immiscible liquids in small channels. 12

13 In liquid-liquid systems, depending on the fluid properties and the channel material, either phase can wet the channel wall, and for phases with similar wettabilities both phases 14 can intermittently adhere to the wall, rendering ordered, stable and well-defined patterns 15 more difficult to form than in gas-liquid flows (Wegmann et al., 2006). Controlling the 16 hydrodynamics could decrease pressure drop, improve mass transfer, and facilitate product 17 separation from the reaction mixture (Dessimoz et al., 2008). Two-phase liquid flows in large 18 channels are mainly dominated by inertia forces and have been investigated using 19 experimentation together with numerical and theoretical modelling (Angeli and Hewitt, 2000 20 Brauner and Maron, 1992). In the case of two-phase flow in microchannels, the interfacial 21 tension and viscous forces are significant because of the small characteristic distances and the 22 low Re numbers (Re < 2000), while gravity and inertia effects become negligible (Kreutzer et 23 24 al., 2005; Foroughi and Kawaji, 2011).

Different patterns can be obtained in microchannels depending not only on 25 26 operational conditions, such as flow rates, phase ratio and properties of the fluids (Lin and Tavlarides, 2009), but also on the geometry of the mixing zone and the channel, and the 27 28 channel wall roughness and wettability (Jovanovic et al., 2011). A highly viscous oil-water system has been investigated by Salim et al. (2008) in microchannels made of quartz and 29 glass and different flow configurations were observed depending on the fluid that was first 30 injected into the test channel. The main flow patterns which have been observed are plug (or 31 32 segmented), drop, annular and parallel flow. The formation of plug and parallel flow is controlled by the competition between viscous and surface tension forces. Plug flow in 33

1 particular has been studied by many investigators (Kashid and Agar, 2007; Garstercki et al., 2006; Dessimoz et al., 2008), utilising both Y- and T-junctions as mixing zones. Moreover, 2 Kashid and Agar (2007) observed that by having fluid mixing zones with different channel 3 diameters, significant changes on the plug size and thus interfacial area were obtained. They 4 found that capillary microreactors provided very large specific interfacial areas in comparison 5 to other contactors, which enhanced mass transfer rates (for water-iodine-kerosene system, 6 $k_{I}\alpha = 1311-9815 \times 10^{-4} \text{ s}^{-1}$, where $k_{I}\alpha$ is the volumetric mass transfer coefficient). Kashid et al. 7 (2005) reported that the intensity of the internal circulations in slugs, during plug flow, and 8 therefore the overall mass transfer rate, depended on slug geometry. Plug flow has been used 9 to enhance mass and heat transfer in a few reactions, such as nitration (Dummann et al., 10 2003). Annular and parallel flows were observed when the inertial forces dominated over the 11 interfacial forces at We > 1 (see Table 1 for a definition of dimensionless numbers) which, 12 however, were easily destabilised by changing flow rates and volumetric flow ratios (Zhao et 13 al. 2006; Dessimoz et al., 2008). A general criterion has been suggested by Kashid and Kiwi-14 Minsker (2011) for an a priori flow pattern identification based on the parameter $\text{Re}_{D}d_{ch}/\epsilon_{D}$. 15 According to the authors, flow patterns were classified into three regions based on the 16 dominant forces. Segmented (plug) flow would occur in the surface tension dominated region 17 for $\text{Re}_{D}d_{ch}/\epsilon_{D} < 0.1$ m; annular flow would occur in the inertia dominated region for 18 $\text{Re}_{D}d_{ch}/\epsilon_{D} > 0.35$ m; transitional patterns (between plug and annular flow) would appear in 19 the transition region for 0.1 m < $\text{Re}_{D}d_{ch}/\epsilon_{D}$ < 0.35 m. The proposed criteria were applied to 20 different microchannel geometries i.e. rectangular, trapezoidal, and concentric, and were 21 22 found to be independent of contacting geometry and cross sectional geometry of the microchannels. 23

Knowledge of pressure drop during two-phase flow in microchannels is also essential 24 for the design of energy efficient systems. There are, however, relatively few studies 25 26 available on pressure drop in liquid-liquid microchannel flows (e.g. Kashid et al., 2007; 27 Chakrabati et al., 2005; Jovanovic et al. 2011) compared to those available for gas-liquid flows (e.g. Kreutzer et al., 2005; Chen et al., 2002; Triplett et al., 1999; Kawahara et al., 28 2002). The models which have been developed for the plug liquid-liquid flow pattern in a 29 microchannel are based to two basic contributions, i.e. the hydrodynamic pressure drop of the 30 two individual phases and the pressure drop due to capillary phenomena. Plug flow is usually 31 modelled as a series of unit cells, composed of a dispersed and a continuous phase (Kashid 32 and Agar, 2007; Jovanovic et al., 2011). 33

1 One of the common applications involving the flow of two immiscible liquids is extraction, which is conventionally carried out using organic solvents. Recently, ionic liquids 2 (ILs) have been suggested as alternatives to organic solvents because of their negligible 3 volatility and flammability at common industrial conditions (Freemantle, 2010; Plechkova 4 and Seddon, 2008), which reduce solvent loss and make them inherently safe and 5 environmentally friendly. Ionic liquids can be considered as salts with low melting points 6 7 (below 100 °C) composed exclusively of ions (Freemantle, 2010). Their properties can be tuned by the choice of the anion and/or the cation, allowing them to be optimised for a 8 particular application (Seddon et al., 2000; Stark and Seddon, 2007). The hydrophobicity of 9 the ionic liquids depends both on the alkyl chain length of the associated cation, and on the 10 nature of the anion. Imidazolium ions, especially 1-alkyl-3-methylimidazolium, are often 11 used as the cation. The bis{(trifluoromethyl)sulfonyl}amide anion, $[N(SO_2CF_3)_2]^{-1}$ (also 12 known as bistriflamide, and abbreviated to [NTf₂]), has become a popular anion choice for 13 synthesising hydrophobic ionic liquids, that are chemically and thermally robust (Bônhote et 14 al., 1996). 15

Although ionic liquids can find a wide variety of industrial applications (chemical 16 industry, pharmaceuticals, nuclear reprocessing, etc), there is a perception that the industrial 17 18 use of ionic liquids is limited by their high costs bringing both real and psychological economic barriers to their wide use (Birdwell et al., 2006; Deetlefs and Seddon, 2006). One 19 approach to circumvent these barriers is by operating within microchannels which require 20 small solvent hold-up. The reduction in solvent volume is compensated by the high 21 efficiencies achieved, because of the thin fluidic films formed in the confined spaces of the 22 small channels, which can significantly reduce mass transfer resistances. Reactions involving 23 ionic liquids have already been tested in microchannels, and yields much higher than in 24 intensely mixed batch processes were found (Pohar et al., 2009). The flow patterns and 25 26 associated pressure drop of two-phase flows involving ionic liquids are expected to be different to those of common organic solvents, because of their generally high viscosities and 27 their higher densities compared to water. 28

The present work aims to investigate the flow patterns and the corresponding pressure drops during the flow of an ionic liquid, 1-butyl-3-methylimidazolium bistriflamide $([C_4mim][NTf_2])$ and de-ionised water in microchannels made from materials that have different wetting characteristics. Moreover, a comparison with existing pressure drop models

- during plug flow was attempted and a modified model was suggested that agreed well with
 the experimental results. This is the first time that such a study has been presented.
- 3

4 2. Experimental set-up and procedure

5

6 2.1. Experimental set-up

7

A schematic of the experimental set up used for the two phase ionic liquid-water flow 8 9 in microchannels is depicted in Fig. 1. It comprises of three main sections: the fluids delivery section in the mixing zone, the flow visualisation section, and the pressure drop measurement 10 11 section. Two syringe-pumps (Aladdin-1000, WPI) fed the two liquids to the mixing zone. The pumps were calibrated and the maximum uncertainty of the flowrates was $\pm 2\%$. Two 12 13 inlet configurations (Y- and T-junction) were used for mixing the fluids, both made of PTFE with all the branches having the same ID (0.5 mm). In the T-junction, the two fluids entered 14 the mixing zone perpendicularly with the water injected along the test channel axis. The 15 angles of the inlets of the Y-junction were 120°. The test channels used in this work were 16 made of two types of Teflon, PFA and Tefzel, with internal diameter (ID) of 220 µm and 17 270 µm respectively, and of borosilicate glass with an internal diameter of 200 µm. The 18 length (L) of all test channels was 100 mm. The internal diameter of the microchannels was 19 measured using a microscope. 20

The flow visualisation section comprised a high-speed camera (Phantom Miro 4) 21 connected to a computer for data storage and a light source. Images were acquired at a 22 distance 80 mm downstream the inlet. For the pressure drop measurements, a differential 23 24 pressure meter Comark C9555 (range: 0 ± 200 kPa, accuracy $\pm 0.2\%$) was used, connected to two pressure ports before and after the microchannel, as illustrated in Fig. 1. To measure the 25 26 pressure drop in the glass microchannel, two side channels (referred as t2 in Fig. 1), with a length of 5 cm each, were added to connect the main channel to the pressure ports. The two 27 28 Teflon microchannels could be connected directly to the pressure meter, and in this case the 29 side channels t2 were removed.

An ionic liquid, $[C_4mim][NTf_2]$, and de-ionised water were used as test fluids. Because the ionic liquid in its pure state absorbs some water, before the experiments started it was stirred with water for 45 min. Saturation with water was confirmed by measuring the viscosities of both pure and saturated ionic liquid with a digital Rheometer DV-III Ultra

1 (Brookfield). Surface and interfacial tensions of the two liquids were measured with a Kruss DSA 100 drop analyser system by the pendant drop method. The liquid was injected from a 2 needle, and a droplet was formed on the tip of the needle. The droplet was then optically 3 observed, and the surface tension was calculated from the shape of the drop using DSAT 4 5 software for DSA 100 system. In order to measure the interfacial tension between the two liquids the needle was immersed into water and a droplet of ionic liquid was formed. The 6 7 properties of the fluids used for the experiments are given in Table 2. The contact angles of 8 the liquids with substrates made from the same materials as the channel walls were also measured using the Kruss DSA 100 system. Both liquid-air-solid and liquid-liquid-solid 9 contact angles were obtained. In the former case a drop of the liquid was placed on top of a 10 flat plate made by borosilicate glass or Teflon in air and the contact angles were found from 11 the still images taken. In the latter case, the plate was immersed in water and the drop of ionic 12 liquid was put on top of it. The measured contact angles are summarised in Table 3. 13

14

15 2.2. Procedure

16

Flow patterns and pressure drop measurements were carried out for different flow 17 rates of the two liquids using both inlets (T- and Y- junction) in all test microchannels. The 18 flow rates of the ionic liquid varied from 0.065 cm³ h⁻¹ to 11.31 cm³ h⁻¹, and those of water 19 from 0.0169 cm³ h⁻¹ to 214.9 cm³ h⁻¹. The ionic liquid volume fraction varied from 0.05 to 20 0.8. In all cases, the flow rate of ionic liquid was kept constant and that of water was either 21 22 increased or decreased. Pressure drop of single phase water and single phase ionic liquid was measured along the microchannels at various flow rates and very good agreement was found 23 24 with the Hagen-Poiseuille equation. The highest Reynolds numbers are expected for singlephase water flow (Re_{Water}) at superficial velocities the same as the mixture velocity ($U_{Mixture}$) 25 26 defined below and were up to 540.

NP

$$28 \qquad U_{\text{Mixture}} = \frac{Q_{\text{IL}} + Q_{\text{Water}}}{A} \tag{1}$$

29

30 where Q_{IL} is the flow rate of ionic liquid, Q_{Water} is the flow rate of water and A_{Channel} is the 31 channel cross sectional area.

Initial experiments with the glass capillary showed that the patterns were highly affected by the phase that initially filled the microchannel. The air-liquid-solid and the liquid-

liquid -solid contact angles (Table 3) reveal that none of the two liquids preferentially wets 1 the glass channel wall; in fact the liquid-liquid-solid angle is $\sim 90^{\circ}$. To ensure that water will 2 be the continuous phase, in a typical experiment the channel was filled with the minimum 3 flow rate of water before the required flow rate of the ionic liquid was introduced. When 4 steady state was reached, the pressure drop was measured and the flow configuration was 5 recorded. Subsequently, the flow rate of water was increased stepwise. 6 After a set of 7 experiments was completed, the same procedure was repeated with the next chosen flow rate of ionic liquid. The same experiments were also performed by injecting the water at its 8 9 maximum flow rate for a particular ionic liquid flow rate and decreasing it stepwise. The flow patterns and pressure drop recorded were the same for both procedures. A few experiments 10 were carried out with the ionic liquid initially filling the channel and indicative results will be 11 discussed. 12

In the case of the Teflon microchannels, the flow patterns were independent of the first injected fluid. Nevertheless, for consistency, the same procedure as with the glass microchannel was followed. Water, however, could not remain as the continuous phase, because (as can be seen from Table 3) the ionic liquid seems to wet more the Teflon microchannels (contact angles less than 90°), and becomes the continuous phase. Flow pattern and pressure drop measurements were recorded for both Teflon microchannels when steady state was reached.

When a set of experiments was completed, the microchannel was cleaned by injecting dichloromethane (CH_2Cl_2) to remove any residual ionic liquid. Air was then injected to dry the channel. This procedure was performed to ensure reproducibility of the experimental conditions.

24

25 3. Results and Discussion

26

27 *3.1. Flow patterns*

28

It was found that the configuration of the inlet, T- or Y- junction, did not affect significantly the flow patterns that were formed or the range they occupied in the flow pattern map. For this reason, only the flow patterns observed with the T-junction will be discussed. In contrast, flow rates, phase volume fraction, and channel wettability had a significant effect on the flow configurations. The main patterns seen in the glass microchannel were plug, plug & drop

train, and dispersed flow. In the Teflon microchannels, the main flow patterns observed were annular, plug and drop flow. These patterns could be further subdivided into regimes that have mixed characteristics and appeared usually at the boundaries between the different patterns. The Bond number varied from 0.013 to 0.024 for the 3 microchannels, indicating that gravitational forces have a negligible effect on the formation of the flow patterns.

6 7

3.1.1. Glass microchannel

8

9 As discussed previously, the flow patterns in the glass microchannel are highly affected by 10 the fluid that first fills the channel. In all flow configurations, water is in contact with the 11 channel wall and is always the continuous phase. The different flow configurations obtained 12 are presented in the flow pattern map in Fig. 2 in terms of overall mixture velocity, U_{Mixture} 13 (Equation 1) against input ionic liquid volume fraction, ε_{IL} (Equation 2).

15
$$\varepsilon_{IL} = \frac{Q_{IL}}{Q_{IL} + Q_{Water}}$$
 (2)

16

14

17 <u>Plug flow</u>

In this pattern, one liquid forms convex shaped plugs (dispersed phase), with lengths 18 longer than the channel diameter that are separated by slugs of the other liquid (continuous 19 phase), while a thin film of the continuous phase surrounds the dispersed plugs (Fig. 3(a)). In 20 the glass microchannels ionic liquid is flowing as the dispersed phase, while water is the 21 continuous phase. Plug length varied depending on the flow rates. Two types of plugs were 22 seen; short size plugs of 0.2-2 mm at low ionic liquid volume fractions (0.05-0.25) and 23 elongated plugs (>2 mm) at high ionic liquid volume fractions (0.5-0.8). In some cases, in 24 agreement with liquid-liquid flow in larger channels, some isolated drops were observed in 25 the slugs between the plugs. As can be seen in Fig. 2, plug flow occupies a large area of the 26 flow pattern map at low and high ionic liquid fractions. At mixture velocities between 0.5-27 1.0 m s^{-1} and ionic liquid volume fractions lower than 0.13, the interfacial forces which are 28 responsible for stabilising the shape of the plugs, are overcome by inertia forces and 29 30 disturbances appeared at the head and tail of the plugs, with undulations forming along the 31 length of the plug (Fig. 3(b)). It was also found that the length of the ionic liquid plugs decreased slightly, and that of the water slugs increased with increasing water flow rate, at a 32

1 constant ionic liquid flow rate. These size variations were more evident at low total flow 2 rates, $U_{\text{Mixture}} < 0.01 \text{ m s}^{-1}$, and ionic liquid volume fractions $\varepsilon_{\text{IL}} > 0.6$ where the plug length 3 varied by 5-10%.

4

5 Plug & drop train flow

The term "plug & drop train" is used to describe the pattern where ionic liquid plugs 6 7 of different sizes and drops are flowing together in a row within the water phase, while there is no distinct water slug, Fig. 3(c). This pattern occurred at ionic liquid volume fractions 8 $\varepsilon_{IL} > 0.5$ and high total flow rates. At $U_{Mixture} > 0.013 \text{ m s}^{-1}$, the number of plugs increased 9 with increasing ionic liquid fraction and their size was irregular, which led to the formation of 10 this pattern. The low interfacial tension between water and ionic liquid, which favours drop 11 break-up could explain the formation of this pattern. It is worth mentioning that, in this 12 pattern, the ionic liquid could also come in contact with the pipe wall. 13

14

15 Intermittent flow (plugs with drops at tail)

The intermittent flow regime is characterised by ionic liquid plugs with drops of 16 various sizes at their tails, Fig. 3(d). It is located mainly at ionic liquid volume fractions 17 $0.33 < \varepsilon_{IL} < 0.5$ and $U_{Mixture} > 0.001 \text{ m s}^{-1}$. This is a transitional pattern between plug and 18 "plug & drop train" flow, or between plug (at low ε_{IL}) and elongated plug (at high ε_{IL}) flow. 19 With increasing total flow rate, the drops at the tails of the plugs become larger. Moreover, at 20 $U_{\text{Mixture}} > 0.012 \text{ m s}^{-1}$ with increasing ionic liquid volume fraction, the drops at the tails of the 21 plugs increase in size and eventually break up into smaller ones, which spread in the water 22 slug and can even reach the front of the following plug, establishing the plug & drop train 23 24 flow.

25

26 Dispersed flow

The dispersed pattern (ionic liquid as dispersed phase, Fig. 3(e), occurs at very high flow rates $U_{\text{Mixture}} > 0.625 \text{ m s}^{-1}$ and for low ionic liquid volume fractions, $\varepsilon_{\text{IL}} < 0.1$. The small interfacial tension that favours drop break-up contributes to this.

30

When ionic liquid came in contact with the tube wall, the flow patterns became disturbed. This particularly happened at low total flow rates. In this case, the channel was cleaned and the series of experiments were repeated. A few experiments were also conducted

with the ionic liquid injected first in the channel instead of water. In this case, ionic liquid 1 became the continuous phase and water was flowing as the dispersed, while the patterns were 2 almost the same as those formed in the Teflon microchannels (see below). For example, 3 throat annular flow with water in the core of the channel (Fig. 3(g)) was detected almost at 4 the same range of mixture velocities. In addition, at high volume fractions, $\varepsilon_{IL} > 0.7$ and high 5 mixture velocities, drop flow was obtained. It is worth mentioning, that the same throat 6 7 annular flow was not found when water was first injected in the glass microchannel and was the continuous phase. Instead at these conditions plug& train flow was observed. This can be 8 9 attributed to the low superficial water flowrates that cannot easily sustain a continuous water film along the channel. In addition when the ionic liquid is the dispersed phase, inertial forces 10 are negligible ($We_{IL} \ll 1$), and do not lead to the formation of an annulus core. At low ionic 11 rates $Q_{\rm IL} < 1.131 \text{ cm}^3 \text{ h}^{-1}$ and for volume fractions liquid flow $\varepsilon_{\rm IL} < 0.330$ 12 $(U_{\text{Mixture}} < 0.030 \text{ m s}^{-1})$, plug flow was formed but there was no continuous phase film 13 surrounding the dispersed plugs. In this case, both phases were alternatingly contacting the 14 channel wall. It is possible that at these conditions, the ionic liquid film surrounding the water 15 slugs is very thin and can easily break up allowing the water plugs to come into contact with 16 the channel wall. 17

18

19 *3.1.2. Teflon microchannels*

20

The flow pattern map obtained with the Teflon microchannels (made from FEP and from Tefzel) can be seen in Fig. 4. The symbols correspond to the FEP microchannel, while the lines correspond to the Tefzel one.

24

25 <u>Plug flow</u>

In the two Teflon microchannels (FEP and Tefzel), as would be expected for hydrophobic channel walls, water forms convex shaped plugs and ionic liquid forms concave slugs; a film of ionic liquid surrounds the water plugs. As can be seen from Fig. 4, plug flow occupies a large area of the flow pattern map for both channels (similar to the glass microchannel). Plug flow is established for a narrower range of mixture velocities and volume fractions for the FEP microchannel compared to the Tefzel one. At low $\varepsilon_{IL} < 0.13$ and 0.006 m s⁻¹ < $U_{Mixture} < 0.055$ m s⁻¹, the plugs in the Tefzel microchannel had irregular sizes.

It was also found that, for a constant ionic liquid flow rate, an increase in the water flow rate, increased the size of water plugs, while that of the ionic liquid slugs was slightly decreased. At volume fraction 0.5, it was found that as the mixture velocity increased, the plugs were decreased in size but increased in number due to the rapid penetration of one phase into the other at the inlet, which breaks the water stream into a larger number of segments. In this way, a high specific interfacial area is achieved that can improve mass transfer rates.

8

9 <u>Annular flow</u>

In annular flow, the lighter of the two phases (water) flows in the centre of the channel (core flow), while the heavier one (ionic liquid) is contained in a thin film wetting the channel wall. Annular flow occurs at high velocities of the water phase, where the inertia of the water is sufficiently high to break through the ionic liquid in slug flow. Depending on mixture velocity and ionic liquid volume fraction different kinds of annular flow, namely quasi, throat and rivulet, were observed (Fig. 3).

In the FEP microchannel, annular flow exists at ionic liquid volume fractions from 16 0.05 to 0.2 and mixture velocities from 0.006 m s⁻¹ to 1.653 m s⁻¹. At U_{Mixture} from 17 0.006 m s^{-1} to 0.063 m s^{-1} , the elongated plugs of water coalesce with each other and create a 18 At higher mixture velocities $0.082 \text{ m s}^{-1} < U_{\text{Mixture}} < 0.330 \text{ m s}^{-1}$, throat core, Fig. 3(f). 19 annular flow was observed, Fig. 3(g). In the Tefzel microchannel, quasi annular flow was not 20 seen, and the throat annular flow was slightly shifted to lower ionic liquid volume fractions 21 and higher mixture velocities compared to the FEP one. In both types of channels, at high 22 $U_{\text{Mixture}} > 0.330 \text{ m s}^{-1}$ and ionic liquid volume fraction $\varepsilon_{\text{IL}} < 0.13$, there is a large velocity 23 difference between the two phases and the interface becomes irregular, leading to the rivulet 24 annular flow, Fig. 3(h), with the core occasionally coming in contact with the channel wall. 25

26

27 <u>Drop flow</u>

The term drop flow, Fig. 3(i), is used to describe a pattern where water drops, with sizes smaller than the channel diameter, are flowing in a row in the channel. This pattern is seen mainly at relatively high mixture velocities and ionic liquid volume fractions, as can be seen in Fig. 4.

- 32
- 33 <u>Irregular flow</u>

Irregular flow, Fig. 3(j), was detected only at high mixture velocities for both microchannels
 and represents a transition between plug and annular flow.

3

4

3.2. Comparison of flow pattern boundaries in the 3 test sections

5

The flow pattern boundaries observed in the three different test sections used in this 6 7 work are compared in Fig. 5. The patterns and their boundaries are similar in the two Teflon microchannels. In the Tefzel channel, the plug flow occupies a slightly larger area of the map 8 compared to the FEP channel, and the boundary to annular flow is shifted to higher mixture 9 velocities and lower ionic liquid volume fractions, while the boundary to drop flow is shifted 10 to slightly higher mixture velocities and ionic liquid volume fractions. Finally, the irregular 11 flow was observed at almost the same mixture velocities in both microchannels, but at lower 12 ionic liquid volume fractions (higher Re numbers of the dispersed water phase) in the Tefzel 13 channel compared to the FEP one. These differences in flow pattern boundaries are attributed 14 to the small differences in the inner diameter between the FEP (ID=220 µm) and Tefzel 15 (ID=270µm) channels, which is in agreement with previous findings (Kashid et al., 2005). In 16 contrast, in the glass microchannel with water as the continuous phase, annular and drop flow 17 18 were not detected. Instead of annular flow, at low ionic liquid volume fractions and high mixture velocities, dispersed flow appeared, while instead of drop flow at high ionic liquid 19 20 volume fractions, plug & drop train flow occurred. The largest area of the map was occupied by some type of plug flow, divided into plug, intermittent and "elongated plug" flow. 21

22 The flow pattern boundaries were compared against the criteria by Kashid and Kiwi-Minsker (2011). It should be noted here that these criteria had been tested against results from 23 24 low viscosity oils. As a result the Re_C/Ca_C numbers where higher compared to those from the present study. According to the criteria, the patterns in the glass capillary with water as the 25 26 continuous phase should all be in the surface tension dominated region ($\text{Re}_{D}d_{ch}/\epsilon_{D} < 0.1 \text{ m}$). 27 This agrees with the experimental observations since no annular flow was found. For the two Teflon microchannels (mainly for the FEP one, with ID=220 µm) plug flow was correctly 28 predicted to fall within the surface tension dominated region ($\text{Re}_{\text{D}}\text{d}_{\text{ch}}/\epsilon_{\text{D}} < 0.1$ m). However, 29 annular flow was predicted to be in the transition (0.1 m $< \text{Re}_{D}d_{ch}/\epsilon_{D} < 0.35$ m) rather than 30 the inertia region ($\text{Re}_{D}d_{ch}/\epsilon_{D} > 0.35$ m). Similar disagreement was found between the model 31 predictions and the experimental results of Salim et al. (2008) who used a highly viscous 32

continuous phase as in the current study resulting in low Re_C/Ca_C numbers; in their case a
 stratified flow inertia regime, was predicted to be within the transition region.

3

4

5

3.3. Plug length measurements

Plug lengths (of water) were measured in the two Teflon microchannels only for the 6 T-junction as inlet, for equal flow rates of the two liquids, using the high-resolution images 7 recorded. The average lengths (over 10 measurements per case) had a deviation of around 8 9 $\pm 6\%$ from the mean value. The data are plotted in Fig. 6 as ratio of plug length over channel diameter versus flow rate of water. As can be seen, in both microchannels the water plug 10 length becomes shorter as the water flow rate increases. This means that the interfacial area 11 increases slowly with increasing flow rate. In addition, the dimensionless plug length is 12 longer in the Tefzel compared to the FEP channel, which means that in the slightly larger 13 Tefzel channel longer plugs formed for the same flow conditions. Interfacial area is therefore 14 increased in the channel with the smallest dimension (FEP). 15

16

17 *3.4. Pressure drop*

18

The pressure drop (ΔP) across a given length of microchannel (100 mm) was 19 20 measured for different flow rates of both phases and various ionic liquid volume fractions, ε_{II} . The data obtained in this work are presented in Figs. 7-9 against input ionic liquid volume 21 22 fraction for constant ionic liquid flow rates. The pressure drop of the single-phase ionic liquid $(\varepsilon_{IL}=1)$, having the same flow rate as the ionic liquid phase in the two-phase mixture, was 23 also measured and presented. For the two Teflon microchannels, the relevant flow patterns 24 established are also shown, while for the glass microchannel pressure drop was only 25 26 measured during plug flow.

27

28 *3.4.1. Teflon microchannels*

29

The pressure drop results for the two Teflon microchannels can be seen in Figs. 7 and 8 for the FEP and the Tefzel materials respectively. Pressure drop was measured at least seven times for each set of conditions, and the mean values were calculated. The deviation from the mean value was very low (on average below $\pm 4\%$) for all cases (the standard

deviation lines cannot be seen in the graphs because they are smaller than the symbols), apart
 from high mixture velocities and low ionic liquid volume fractions where the deviation was
 between 5.5-12%.

In the FEP channel, pressure gradients are very similar for both the T- and Y- junction 4 inlets used, Figs. 7(a) and 7(b). As expected at a constant flow rate of ionic liquid, an increase 5 in the water flow rate (decrease in the ionic liquid volume fraction) led to an increase in the 6 7 measured pressure drop, because the mixture flow rate increased. At higher ionic liquid flowrates the increase became more prominent when annular flow established. When the 8 pattern changes from plug to annular for the same ionic liquid flowrate, the ionic liquid is 9 restricted to a smaller part of the cross section and its velocity will be increased resulting in 10 higher frictional pressure drop. Interestingly, at ionic liquid flow rate of 5.655 cm³ h^{-1} and at 11 low ionic liquid volume fractions, this trend is reversed and a decrease in the two-phase 12 pressure drop was observed. This happens during annular flow when the pattern changes 13 from throat to rivulet annular and water, that has a lubricating effect, comes in contact with 14 the channel wall. In the case of $Q_{\rm IL} = 8.483 \text{ cm}^3 \text{ h}^{-1}$, the pressure drop at low ionic liquid 15 volume fractions was not measured because it was outside the range of the pressure meter 16 17 used.

Similar results for both inlets were also found in the Tefzel channel and are presented in Fig. 8 for the T-junction. Pressure drop increases with increasing water flow rate, similar to the FEP microchannel. This increase is more profound at ionic liquid flow rates higher than $5.655 \text{ cm}^3 \text{ h}^{-1}$.

22

23 3.4.2. Glass microchannel

24

In the glass microchannel, pressure drops were measured only for ionic liquid volume 25 fractions between 0.05-0.42 where short plugs were detected. As found for the Teflon 26 27 microchannels, the pressure drop is similar for both inlet configurations and increases with increasing water flow rate (Fig. 9 for the T-junction). However, in the glass microchannel, 28 the pressure drop of single phase flow ionic liquid at the same flow rate as in the mixture is 29 always higher than the pressure drop of the two-phase mixture. This is because, in the glass 30 microchannel, the phase in contact with the channel wall is the low viscosity water. High 31 values of pressure drop, approaching those of single-phase water, were obtained at flow rates 32 $Q_{\rm IL} > 5.655 \text{ cm}^3 \text{ h}^{-1}$ and low $\varepsilon_{\rm IL}$, but were still less than those of single-phase ionic liquid. In 33

the case of the glass microchannel, the deviation from the mean value was in all cases very low. These findings are very important because they demonstrate that the high viscosities of the ionic liquids are not limiting factors for their use in small channels, provided suitable flow patterns are established.

5 Some indicative experiments were performed in the glass microchannel when the 6 ionic liquid was the continuous phase. In this case, pressure drop was found to be higher than 7 that of single phase ionic liquid as is the case for the two Teflon microchannels.

8

9 3.5. Comparison of the pressure drop for the 3 test sections

10

The pressure drops for the three different microchannels are compared in Fig. 10 for a 11 constant ionic liquid flow rate of $Q_{\rm IL} = 2.262 \text{ cm}^3 \text{ h}^{-1}$. Because of the small differences in the 12 diameters of the three channels, to enable the comparisons the data have been non-13 dimensionalised by dividing the two-phase pressure drop with that of the ionic liquid flowing 14 alone in the channel (η). As can be seen in Fig. 10, the dimensionless pressure drop (η) in the 15 two Teflon microchannels is higher than in glass. This can be explained by the fact that in the 16 two Teflon microchannels, the continuous phase is the ionic liquid which has higher viscosity 17 and, therefore, causes higher frictional pressure drop than water which is the continuous 18 phase in the glass microchannel. It was also observed that, in all cases, η decreases as the 19 ionic liquid volume fraction increases. This decrease is more obvious at low $\varepsilon_{IL} < 0.25$. 20

In the case of the two Teflon microchannels, it is seen that the dimensionless pressure 21 drop for the FEP channel is higher over the whole range of ionic liquid volume fractions 22 studied. During plug flow ($\varepsilon_{IL} > 0.25$), this difference is attributed to the number of slugs 23 present. As was discussed in Section 3.3, compared to the FEP channel, under the same phase 24 flow rates longer plugs are formed in the Tefzel channel, and their number is reduced; this 25 will result in a lower capillary pressure drop contribution to the overall pressure drop 26 (Jovanovic et al., 2011). At lower ionic liquid volume fractions ($\varepsilon_{IL} < 0.25$), the difference of 27 the dimensionless pressure drop between the two Teflon microchannels is higher. In the FEP 28 channel, annular flow starts just below $\varepsilon_{IL} < 0.25$, explaining the increase in pressure drop at 29 this volume fraction. In the Tefzel channel, the flow remains plug until $\varepsilon_{IL} = 0.1$, where it 30 becomes irregular (with both plug and annular flow characteristics); annular flow establishes 31 only at $\varepsilon_{IL} < 0.08$ where the increase in pressure drop is seen. 32

1 3.6 Comparison with pressure drop models

2

The drop measurements during plug flow in the Tefzel microchannel are compared 3 with the existing models of Kashid and Agar (2007b) and Jovanovic et al. (2011). As was 4 mentioned before, in the Tefzel channel ionic liquid was the continuous phase that formed a 5 film around the dispersed water plugs. In both works, plug flow is considered as a series of 6 7 unit cells, alternatingly occupied by each phase. Kashid and Agar (2007b) do not consider the film that surrounds the plugs and suggest that pressure drop is equal to the frictional pressure 8 drop of the dispersed and of the continuous phases, and of the interfacial pressure drop (Eq. 9 3). 10

11

12
$$\Delta P_{\text{plug flow}} = \Delta P_{\text{Frictional}} + \Delta P_{\text{Interfacial}} = (\Delta P_{\text{Fr,c}} + \Delta P_{\text{Fr,d}}) + \Delta P_{\text{I}}$$
 (3)

13

The frictional pressure drop is calculated from the Hagen-Poiseuille equation, while the 14 interfacial pressure drop from the Young-Laplace equation. The predictions of this model are 15 compared against the experimental data from this work in Fig. 11. The interfacial pressure 16 drop was calculated using the measured static liquid-liquid-solid contact angles. Agreement is 17 found only at low mixture velocities. At these velocities where the ionic liquid film is very 18 thin and expected to be almost stagnant, the contribution of the dispersed water phase seems 19 to be predicted correctly. At higher velocities and higher Ca numbers, however, the ionic 20 liquid film thickness increases and would have some velocity, causing additional frictional 21 22 pressure drop. Since the model assumes that the less viscous water comes in contact with the wall periodically, it underestimates the frictional pressure drop in the slug part of the flow 23 24 which should depend on the combination of ionic liquid wall and interfacial shear stresses. In addition, as We number increases the interfacial forces become week and the plugs cannot 25 26 maintain their shape; the front part elongates whilst the back end flattens (Dore et al., 2012). 27 This leads to deviations from the pressure drop calculated for a static contact angle.

In their model Jovanovic et al. (2011) included the film around the slugs. They found 28 that the influence of the film velocity on the plug pressure drop is negligible (lower than 29 30 1.4%) and suggested the following equation for stagnant film

32
$$\Delta P_{\text{plug flow}} = \frac{8U_{\text{slug}}\mu_{d}aL}{(R-h_{\text{film}})^{2}} + \frac{8U_{\text{mix}}\mu_{c}(1-\alpha)L}{R^{2}} + \frac{L}{l_{u}}C(3Ca)^{2/3}\frac{\gamma}{d}$$
(5)

1		
2	The film thickness was estin	nated using Bretherton's equation (Bretherton, 1961)
3		
4	$h_{\rm film} = 1.34 \rm RCa^{2/3}$	(4)

whilst in systems, where the continuous phase has a considerably higher viscosity that the dispersed phase a correction factor of $2^{2/3}$ was applied (Bico and Quere, 2000). For semispherical plug caps, the constant C, which accounts for the influence of the interface

curvature, was found to be 7.16 (Bretherton, 1961).

The comparisons between experimental pressure drop data during plug flow in the 10 Tefzel microchannel and the stagnant film model (Eq. 5) are shown in Fig. 12. Good 11 agreement was only found at low flow rates. Bretherton's equation for film thickness 12 (corrected by the factor proposed by Bico and Quere, 2000) that was used in the Jovanovic 13 14 equation is not valid for high capillary numbers and film thickness larger than 1% of the channel radius. Clearly film thickness has an important effect on pressure drop. Previously 15 we had reported that current correlations are not able to predict the film thicknesses in ionic-16 liquid water flow in microchannels and suggested a new correlation (Dore et al, 2012), given 17 18 by

19

5

6

7

8

9

 $\frac{h_{film}}{R} = 0.30(1 - e^{-6.90Ca^{0.54}})$ 20

21

As can be seen in Fig. 13, pressure drops predicted using the film thickness calculated by 22 equation (6) agree very well with the experimental data (mean relative error $\sim 8\%$). The new 23 model was able to predict pressure drop during plug flow in all channels tested within 14%. 24

(6)

25

4. Conclusions 26

27

The flow patterns and pressure drop of the two-phase flow of a hydrophobic ionic 28 liquid $[C_4 mim][NTf_2]$ and de-ionised water were investigated in capillaries. For the 29 experiments, three different test section materials were used, two types of Teflon (FEP and 30 31 Tefzel) that are both preferentially wetted by the ionic liquid, and glass that is similarly wetted by both phases. 32

1 In all cases studied, the inlet configuration (T- or Y- junction) did not affect the flow patterns or pressure drop. In the glass microchannel, the patterns were highly affected by the 2 phase that initially filled the channel. The main flow patterns observed were plug flow with 3 ionic liquid plugs, intermittent flow with ionic liquid drops at the tail of the plug, and "plug & 4 drop train" flow where ionic liquid plugs and drops were flowing together in a row along the 5 microchannel within a water continuous phase. In the two Teflon microchannels, the main 6 flow patterns were annular (water in core) at low ionic liquid volume fractions, with plug and 7 drop flow (with water plugs in both cases). In addition, plug length measurements in the 8 Teflon microchannels showed that plug length decreases with increasing total flow rate. 9

Pressure drop in the Teflon microchannels, at a constant ionic liquid flow rate, was 10 found to increase as the ionic liquid volume fraction decreased and was always higher than 11 the single phase ionic liquid value at the same flow rate as in the two-phase mixture. At high 12 ionic liquid flow rates and low ε_{IL} (< 0.13), a larger increase in pressure drop was seen which 13 was attributed to the change in the pattern from plug to annular. This was followed by a 14 decrease in pressure drop when the pattern changed from throat to rivulet annular flow. 15 Differences in the pressure drops between the two Teflon microchannels during plug flow 16 were attributed to different plug lengths. In the glass microchannel during plug flow with the 17 water as the continuous phase, pressure drop for a constant ionic liquid flow rate was always 18 significantly lower than the single phase ionic liquid value at the same flow rate as in the 19 20 mixture velocity. The pressure drop was, however affected by the phase which initially filled the channel. It was also found that when an improved correlation for film thickness was used 21 22 in a plug flow pressure drop model, there was very good agreement with the experimental results. 23

24

25 **References**

Angeli P., Hewitt G.F., 2000. Flow structure in horizontal oil-water flow. Int. J. Mul. Fl., 22,
7, 1117-1140

- 28 Angeli P., Gavriilidis A., 2008.Hydrodynamics of Taylor flow in small channels: a review.
- 29 Proc. Inst. Mech. Eng. Part C, J. Mech. Eng. Sci. 222 (5), 737-751.
- 30 Birdwell J.F., McFarlane J., Hunt R.D., Luo H., DePaoli D.W., 2006. Separation of ionic
- liquid dispersions in centrifugal solvent extraction contactors. Sep. Sci. Technol. 41, 22052223.

- 1 Bônhote, P., Dias, A.P., Papageorgiou, N., Kalyanasundaram, K., Grätzel, M. 1996.
- 2 Hydrophobic, highly conductive ambient-temperature molten salts. Inorg. Chem. 35, 1168-
- 3 1178.
- 4 Brauner N., Maron D.M., 1992. Stability analysis of stratified liquid-liquid flow. Int. J.
- 5 Multiphase Flow, Vol. 18, No. 1, 103-121
- 6 Bretherton F.P., 1961. The motion of long bubbles in tubes. J. Fluid Mech. 10, 166-168.
- 7 Chakrabati D.P., Das G., Ray S., 2005. Pressure drop in liquid-liquid two phase horizontal
- 8 flow: experiment and prediction. Chem. Eng. Technol. 28, No 9.
- 9 Chen I.Y., Yang K.S., Wang C.C., 2002. An empirical correlation for two-phase frictional
- 10 performance in small diameter tubes. Int. J. Heat Mass Transfer 45, 3667-3671.
- 11 Deetlefs, M., Seddon, K.R., 2006. Ionic liquids: fact and fiction, Chim Oggi Chem. Today
- 12 24 [Mar-Apr], 16-23.
- 13 Dessimoz A., Cavin L., Renken A., Kiwi-Minsker L., 2008. Liquid-liquid two-phase flow
- 14 patterns and mass transfer characteristics in rectangular glass microreactors. Chem. Eng. Sci.
- 15 63, 4035-4044.
- 16 Dummann G., Quittmann U., Groschel, Agar David W., Worz O., Morgenschweis K., 2003.
- The capillary-microreactor: a new reactor concept for the intensification of heat and masstransfer in liquid-liquid reactions. Catal. Today 79-80, 433-439.
- 19 Foroughi H., Kawaji M., 2011. Viscous oil-water flows in a microchannels initially saturated
- with oil: Flow patterns and pressure drop characteristics. Int. J. Multiphase Flow, 37, 11471155.
- 22 Freemantle, M., 2010. An Introduction to Ionic Liquids. RSC Publications, Cambridge, UK.
- Garstecki P., Fuerstman M.J., Stonec H.A., Whitesides G.M., 2006. Formation of droplets
 and bubbles in a microfluidic T-junction-scaling and mechanism break-up. Lab Chip 6, 437446.
- Jovanovic J., Zhou W., Rebrov E.V., Nijhuis T.A., Hessel V., Schouten J.C., 2011. Liquidliquid slug flow: Hydrodynamics and pressure drop. Chem. Eng. Sci. 66, 42-54.
- 28 Kashid M.N, Gerlach I., Goetz S., Franzke J., Acker J.F., Platte F., Agar D.W., Turek S.,
- 2005. Internal circulation within the liquid slugs of a liquid-liquid slug-flow capillary
 microreactor. Ind. Eng. Chem. Res. 44, 5003-5010.
- 31 Kashid M.N, Harshe Y.M., Agar D.W., 2007. Liquid-liquid slug flow in a capillary: an
- alternative to suspended drop or film contactors. Ind. Eng. Chem. Res. 46, 8420-8430.

- Kashid M.N, Agar D.W., 2007. Hydrodynamics of liquid-liquid slug flow capillary
 microreactor: flow regimes, slug size and pressure drop. Chem. Eng. J. 131, 1-13.
- 3 Kashid M.N., Kiwi-Minsker L., 2011. Quantitative prediction of flow patterns in liquid-liquid
- 4 flow in microcapillaries. Chem. Eng. Proc., 50, 972-978
- 5 Kawahara A., Chung P.M.Y., Kawaji M., 2002. Investigation of two phase flow pattern, void
- 6 fraction and pressure drop in a microchannel. Int. J. Multiphase Flow 28, 1411-1435.
- 7 Kreutzer M.T., Kapteijn F., Moulijin J.A., Heiszwolf J.J., 2005. Multiphase monolith
- 8 reactors: chemical reaction engineering of segmented flow in microchannels. Chem. Eng. Sci.
- 9 60, 5895-5916.
- 10 Lin R., Tavlarides, L.L., 2009. Flow patterns of *n*-hexadecane-CO₂ liquid-liquid two-phase
- 11 flow in vertical pipes under high pressure. Int. J. Multiphase Flow 30, 225-236.

12 Plechkova, N.V., Seddon, K.R., 2008. Applications of ionic liquids in the chemical industry.

- 13 Chem. Soc. Rev. 37, 123-150.
- 14 Pohar A., Plazl I., Plazl P.Z., 2009. Lipase-catalyzed synthesis of isoamyl acetate in an ionic
- 15 liquid/*n*-heptane two-phase system at the microreactor scale. Lab Chip 9, 3385-3390.
- 16 Salim A., Fourar M., Pironon J., Sausse J., 2008. Oil-water two-phase flow in microchannels:
- 17 flow patterns and pressure drop measurements. Can. J. Chem. Eng. 86, 978-988.
- Seddon, K.R., Stark, A., Torres, M.J., 2000. Influence of chloride, water and organic solvents
 on the physical properties of ionic liquids. Pure Appl. Chem. 72, 2275-2287.
- 20 Stark, A., Seddon, K.R., 2007. Ionic Liquids, in Kirk-Othmer Encyclopaedia of Chemical
- *Technology*, 5th Edit., Ed. Seidel, A., Vol. 26. John Wiley & Sons, Inc., Hoboken, New
 Jersey, 836-920.
- 23 Triplett K.A., Ghiaasiaan S.M., Abdel-Khalik S.I., LeMouel A., McCord B.N. Gas-Liquid
- 24 two-phase flow in microchannels, Part II: void fraction and pressure drop. Int. Multiphase
- 25 Flow 25, 395-410.
- Wegmann A., von Rohr P.R., 2006. Two-phase liquid-liquid flows in pipes of small
 diameters. Int. J. Multiphase Flow 32, 1017-1028.
- Zhao Y., Chen G., Yuan Q., 2006. Liquid-liquid two-phase flow patterns in a rectangular
 microchannel. A.l.Ch.E Journal 52, 4052-4060.
- 30
- 31
- 32
- 52



3 Fig. 1. Schematic of the experimental set-up.



1 2



Fig 3. Photographs of ionic liquid-water two-phase flow patterns in microchannels for various mixture velocities and phase volume fractions.



Fig. 4. Ionic liquid-water flow patterns in the two Teflon, FEP and Tefzel, microchannels with a T-junction inlet. FEP: symbols, Tefzel: lines.



Fig. 5. Comparison of the flow pattern boundaries in the FEP, Tefzel and glass microchannels with a T-junction as inlet.

R



Fig. 6. Average water plug length to channel diameter ratio versus water flow rate in the two Teflon microchannels with a T-junction as inlet for equal water and ionic liquid flow rates.



Fig. 7. Two-phase pressure drop versus input ionic liquid volume fraction at different ionic liquid flow rates for the FEP microchannel and (a) T-junction, (b) Y-junction inlet. Q_{IL} : (1) = 1.131 cm³ h⁻¹, (2) = 2.262 cm³ h⁻¹, (3) = 5.655 cm³ h⁻¹, (4) = 8.482 cm³ h⁻¹ Flow pattern symbols: Annular (+), Plug (\blacksquare), Drop (\circ), Irregular (Δ)



Fig. 8. Two-phase pressure drop versus input ionic liquid volume fraction at different ionic liquid flow rates for the Tefzel microchannel with T-junction as inlet.

 $Q_{IL}: (1) = 1.131 \text{ cm}^3 \text{ h}^{-1}, (2) = 2.262 \text{ cm}^3 \text{ h}^{-1}, (3) = 5.655 \text{ cm}^3 \text{ h}^{-1}, (4) = 8.482 \text{ cm}^3 \text{ h}^{-1}, (5) = 11.31 \text{ cm}^3 \text{ h}^{-1}$

Flow pattern symbols: Annular (+), Plug (\blacksquare), Drop (\circ), Irregular (Δ)

Rock



Fig. 9. Two-phase pressure drop versus input ionic liquid volume fraction during plug flow at different ionic liquid flow rates for the glass microchannel with a T-junction as inlet. The pressure drop values for single phase ionic liquid are given on the right

 $Q_{IL}: (1) = 1.131 \text{ cm}^3 \text{ h}^{-1}, (2) = 2.262 \text{ cm}^3 \text{ h}^{-1}, (3) = 5.655 \text{ cm}^3 \text{ h}^{-1}, (4) = 8.482 \text{ cm}^3 \text{ h}^{-1}, (5) = 11.31 \text{ cm}^3 \text{ h}^{-1}, (6) = 11.31 \text{ cm}^3 \text{ h}^{-1}$



Fig. 10. Comparison of non-dimensional pressure drop in the FEP, Tefzel and glass microchannels with a T-junction as inlet, at a constant ionic liquid flow rate, $Q_{\rm IL} = 2.262 \text{ cm}^3 \text{ h}^{-1}$.



Fig. 11. Comparison of the pressure drop measurements obtained experimentally during plug flow with Kashid model. Symbols correspond to experimental data: Δ - Q_{IL} =2.262 cm³ h⁻¹; \Box - Q_{IL} =5.482 cm³ h⁻¹; \Diamond - Q_{IL} =8.482 cm³ h⁻¹. Filled symbols correspond to theoretical values.

31



Input ionic liquid volume fraction, $\epsilon_{\rm IL}$ / -

Fig. 12. Comparison of the pressure drop measurements obtained experimentally during plug flow with Jovanovic model. Symbols correspond to experimental data: Δ - Q_{IL}=2.262 cm³ h⁻¹; \Box - Q_{IL}=5.482 cm³ h⁻¹; \Diamond - Q_{IL}=8.482 cm³ h⁻¹. Filled symbols correspond to theoretical values.



Fig. 13. Comparison of the pressure drop measurements obtained experimentally during plug flow with modified Jovanovic model. Symbols correspond to experimental data: Δ - Q_{IL} =2.262 cm³ h⁻¹; \Box - Q_{IL} =5.482 cm³ h⁻¹; \diamond - Q_{IL} =8.482 cm³ h⁻¹. Filled symbols correspond to theoretical values.

Dimensionless numbers	Definition		
Reynolds number	$Re_{i} = \frac{\rho_{i}U_{i}ID}{\mu_{i}} = \frac{\text{inertia forces}}{\text{viscous forces}}$		
Capillary number	$Ca_i = \frac{\mu_i U_i}{\gamma} = \frac{viscous \text{ forces}}{interfacial forces}$		
Weber number	$We_i = \frac{\rho_i U_i^2 ID}{\gamma} = \frac{inertia \text{ forces}}{interfacial \text{ forces}}$		
Bond number	$Bo = \frac{ID^2 \Delta \rho g}{\gamma} = \frac{buoyancy forces}{interfacial forces}$		

Table 1. Dimensionless number for the characterisation of the two-phase flow.

Table 2. Properties of the test liquids.

	[C ₄ mim][NTf ₂]			
Properties (20 °C)	Pure	Water	Deionised Water	
		saturated	0	
Viscosity, $\mu / \text{kg m}^{-1} \text{ s}^{-1}$	0.052	0.041	0.001	
Surface tension, $\sigma / N m^{-1}$	31.26.10-3	31.55.10-3	73.14.10-3	
Density, $\rho / \text{kg m}^{-3}$	1420		1000	
Interfacial tension, $\gamma / N m^{-1}$	12.29.10-3			
A CORPTER MANUE				

Table 3. Contact angles (θ °) on a borosilicate glass and Teflon plate.

Fluid 2 Fluid 1 0 ° Surface	[C ₄ mim][NTf ₂]- Deionised water	[C ₄ mim][NTf ₂]- Air	Deionised water-Air	
Borosilicate glass	94°	43°	55°	
Teflon	70°	64°	102°	

Research highlights

- Flow patterns and pressure drop during ionic liquid-water flow in microchannels. •
- Effect of channel wall wetting properties on flow patterns and pressure drop. •
- Pressure drop in plug flow can be lower than that of single phase ionic liquids. •
- Pressure drop in plug flow can be predicted from available models when experimental • film thickness values are used.