



**QUEEN'S
UNIVERSITY
BELFAST**

ICRH assisted breakdown study on JET

Sun, H. J., Wauters, T., Lomas, P. J., Lerche, E., Noble, C., De Vries, P. C., Silburn, S., Kim, H. T., Kirov, K., Coffey, I., Siren, P., Thomas, B., Boboc, A., Palamartchouk, K., Szepesi, G., Joffrin, E., Labit, B., McDonald, D. C., & JET Contributors (2023). ICRH assisted breakdown study on JET. *Plasma Physics and Controlled Fusion*, 65(9), Article 095009. <https://doi.org/10.1088/1361-6587/ace6d2>

Published in:

Plasma Physics and Controlled Fusion

Document Version:

Publisher's PDF, also known as Version of record

Queen's University Belfast - Research Portal:

[Link to publication record in Queen's University Belfast Research Portal](#)

Publisher rights

Copyright 2023 The Authors.

This is an open access article published under a Creative Commons Attribution License (<https://creativecommons.org/licenses/by/4.0/>), which permits unrestricted use, distribution and reproduction in any medium, provided the author and source are cited.

General rights

Copyright for the publications made accessible via the Queen's University Belfast Research Portal is retained by the author(s) and / or other copyright owners and it is a condition of accessing these publications that users recognise and abide by the legal requirements associated with these rights.





Take down policy

The Research Portal is Queen's institutional repository that provides access to Queen's research output. Every effort has been made to ensure that content in the Research Portal does not infringe any person's rights, or applicable UK laws. If you discover content in the Research Portal that you believe breaches copyright or violates any law, please contact openaccess@qub.ac.uk.

Open Access

This research has been made openly available by Queen's academics and its Open Research team. We would love to hear how access to this research benefits you. – Share your feedback with us: <http://go.qub.ac.uk/oa-feedback>

ICRH assisted breakdown study on JET

H J Sun^{1,*} , T Wauters² , P J Lomas¹, E Lerche³, I Monakhov¹, C Noble¹, P C De Vries² , S Silburn¹, H T Kim¹, K Kirov¹, I Coffey⁴, P Siren¹, B Thomas¹, A Boboc¹, K Palamartchouk¹, G Szepesi¹, E Joffrin⁵, B Labit⁶ , D C McDonald¹ and JET Contributors⁷

¹ United Kingdom Atomic Energy Authority, Abingdon, United Kingdom

² ITER Organization, Route de Vinon-sur-Verdon, CS, 90 046, 13067 St. Paul Lez Durance Cedex, France

³ Laboratory for Plasma Physics LPP-ERM/KMS, B-1000 Brussels, Belgium

⁴ Astrophysics Research Centre, School of Mathematics and Physics, Queen's University, Belfast BT7 1NN, United Kingdom

⁵ CEA, IRFM, F-13108 Saint Paul Lez Durance, France

⁶ Ecole Polytechnique Fédérale de Lausanne (EPFL), Swiss Plasma Center (SPC), CH-1015 Lausanne, Switzerland

E-mail: HongJuan.SUN@UKAEA.UK

Received 26 March 2023, revised 25 June 2023

Accepted for publication 12 July 2023

Published 28 July 2023



Abstract

Ion cyclotron (IC) wave assisted breakdown has the potential to increase the robustness of plasma initiation during the ITER pre-fusion operation phase. Studies were performed at JET at ITER relevant loop electric field, $E_{\text{loop}} \lesssim 0.33 \text{ Vm}^{-1}$, and a range of toroidal fields, including at the low toroidal field of 1.7 T for which breakdown had not been achieved previously on JET. The study covered a range of H₂ and D₂ gas prefill pressures and timings, pumping conditions, and residual impurity levels. IC assisted breakdown was achieved for a lower and wider range of gas prefill pressures. IC assisted breakdown works by activating wall pumping before the current rise, changing the relation between fuelling and torus pressure in this phase compared to Ohmic breakdown. IC assisted breakdown enables plasma initiation with a higher level and significantly wider range of injected plasma prefill gas. As the injected prefill gas is the controlled parameter, this significantly improves the robustness of plasma initiation operationally. IC assistance is found to be more robust at ITER-like E_{loop} , succeeding with higher low-Z impurity content. Moreover, it does not introduce an impurity source that may hamper the subsequent burn through and current ramp-up phase. For both the IC assisted and pure Ohmic breakdown, the initial current rise rate is found to scale with n_e/E_{loop} . The results and implications for ITER are presented.

Keywords: plasma initiation, IC assisted breakdown, plasma burn through

(Some figures may appear in colour only in the online journal)

⁷ See the author list of Mailloux *J et al* 2022 *Nucl. Fusion* **62** 042026

* Author to whom any correspondence should be addressed.



Original content from this work may be used under the terms of the [Creative Commons Attribution 4.0 licence](https://creativecommons.org/licenses/by/4.0/). Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

1. Introduction

Plasma initiation in a tokamak begins with a Townsend avalanche phase where residual electrons in the vacuum vessel are accelerated by an induced toroidal electric field, producing secondary electrons through collisional ionisation of prefilled neutrals. This is followed by a burn through phase where, locally, most atoms are stripped of their electrons and the temperature of the plasma is increased through Ohmic heating until the plasma energy losses from interaction with neutrals (electron impact reactions and charge exchange collisions) become small with respect to thermal losses. Predicting the criteria and evolution of breakdown and burn through requires detailed modelling [1], but can be approximated by the Townsend avalanche breakdown criteria:

$$\frac{L_f}{\lambda_i} \gg 1 \quad \text{with} \quad \lambda_i = \left(\frac{a}{p}\right) e^{bp/E_{\text{loop}}} \quad (1)$$

where L_f is the average length of open magnetic field lines (i.e. effective connection length), λ_i the mean length for an electron to be accelerated and make a collisional ionisation of a neutral particle, p is the prefill gas pressure, E_{loop} is the toroidal (loop) electric field, and a and b are constants [2] which, at room temperature (300 K) for H_2 , D_2 , or T_2 , are taken as $a = 0.258 \text{ mPa}^{-1}$ and $b = 950 \text{ Vm}^{-1} \text{ Pa}^{-1}$ [3]. Based on the equation, L_f/λ_i can be used as a predictor for successful plasma breakdown. The breakdown criteria of equation (1) can be seen to have an optimal pressure but increasing E_{loop} is always favourable for breakdown and lower E_{loop} unfavourable with the range of allowable prefill pressures decreasing with decreasing E_{loop} until a value of E_{loop} below which no breakdown is possible. The maximum E_{loop} for ITER is expected to be 0.33 Vm^{-1} which is considerably lower than that of existing tokamak (for JET $E_{\text{loop}} \lesssim 1 \text{ Vm}^{-1}$). This implies relatively long λ_i and so presents a challenge for plasma initiation in ITER. Purely Ohmic plasma initiation is sufficient for JET and many existing tokamaks. Studies indicate that Ohmic plasma initiation in ITER may be challenging in the case of a high hydrogenic background pressure or when there are large amounts of residual in-vessel impurities such as those that may be injected for plasma optimisation or disruption mitigation [1, 4]. This has motivated the study of electron cyclotron (EC) wave assisted plasma initiation both applying EC power to form a pre-ionised plasma prior to Ohmic breakdown and applying EC heating power later to assist the burn through phase. These studies have demonstrated EC assisted plasma initiation on several machines [2, 5–9] and provided a physics basis from which it has been concluded that the method can improve the reliability of plasma initiation on ITER [1, 3, 10].

During the initial ITER pre-fusion plasma operation phase (PFPO-1), ITER will operate at low magnetic field ($B_t = 1.8 \text{ T}$) to enable H-mode access, for which the required heating power has been found empirically to scale near linearly with magnetic field, for H plasma. As the connection length scales linearly with B_t , plasma initiation will be less robust than for the later ITER Fusion Plasma Operation phase. Moreover, studies have shown that the planned 170 GHz ITER

EC system will not be able to effectively heat at the third harmonic resonance that would be required at $B_t = 1.8 \text{ T}$ [11]. As is the case at higher field, Ohmic plasma initiation for ITER at 1.8 T is expected to be adequate, but ion cyclotron (IC) wave assisted breakdown would reduce risk of failed plasma initiation in the case of poor vacuum conditions [1]. Even though the present ITER research plan does not foresee IC heating capabilities for PFPO-1, a case for IC assisted breakdown needs to be developed. This motivates the present study which aims to demonstrate and optimise the method on JET and provide a physics basis for extrapolation to ITER. IC plasma formation has previously been demonstrated and optimised at JET for wall cleaning [12] and a reduction in flux consumption is observed when ICRH is applied in the lower toroidal look voltage case [13].

The structure of this paper is as follows. Section 2 outlines the experimental method used for the studies. Section 3 presents the experimental results related to the criteria for successful plasma initiation. Section 4 presents the results related to the subsequent evolution of the plasma. In section 5, the results are summarised, and their implications discussed.

2. Experimental method

JET plasma initiation is performed [14] by using a set of poloidal field coils to generate a hexapole null in the poloidal field inside the vacuum vessel at the instance when the loop voltage, induced by the central solenoid, has reached its set steady value. In the region around the null, poloidal fields are small, hence the connection lengths are long and so favourable for breakdown. Once an initial plasma carrying a current higher than a few kA is established, the central solenoid controls the plasma current and the poloidal field coils control the plasma position and shape until the required plasma configuration is established.

Figure 1 shows the waveform used for the IC assisted breakdown experiments. Breakdown is initially avoided by applying, from $t = -1 \text{ s}$, a vertical magnetic field which ensures a short connection length. The required E_{loop} and prefill gas pressure is then developed. The applied vertical magnetic field is removed at $t = 0.45 \text{ s}$ and breakdown attempted. The exact time of the breakdown and its development depends upon the experimental conditions. A plasma current waveform is requested from $t = 0.45 \text{ s}$ and the JET plasma control system essentially limits E_{loop} to deliver this current. Before $t = 0.8 \text{ s}$, the requested plasma current is kept low to avoid a strong increase in the loop voltage. The feed forward request of the loop voltage is gradually reduced over 200 ms to obtain a fully feedback controlled electric field at or before $t = 0.8 \text{ s}$. During this time, the breakdown and burn through phases evolve freely. From $t = 0.8 \text{ s}$, the requested plasma current is raised and E_{loop} is controlled to deliver this. As the plasma resistivity is low at this time, the required electric field is well below the 0.33 Vm^{-1} limit of ITER.

Following previous studies of IC discharges for IC wall conditioning (ICWC) in JET [12], the IC frequency is selected for an on-axis fundamental H resonance with the,




Figure 1. Schematic of a JET ion cyclotron (IC) assisted breakdown.

toroidally distributed, antenna straps all in phase—referred to as ‘monopole’ phasing. The resulting IC heating scheme is H minority for D plasma and H majority for H plasma. The antenna protection settings are identical to those for JET ICWC operation, following [12]. The interlock for the pressure in the IC vacuum transmission lines is lowered to 5 mPa with the same limit for the torus pressure. The number of trips per IC amplifier is limited to 10 per discharge and 100 per experimental session. The maximum permitted Voltage Standing Wave Ratio for the IC antenna is increased, but the maximum permitted voltages on the transmission lines is limited to 20 kV. The external conjugate-T matching system is not used. The same injected power was used throughout.

Following the JET ICWC scheme, pre-fill gas fuelling is from valves in the divertor for all discharges to avoid fuelling gas too close to an IC antenna and to obtain a uniform torus pressure. This contrasts with the mid-plane pre-fill gas fuelling more commonly used for breakdown. Compared to mid-plane fuelling, divertor fuelling on JET requires more injected gas to produce the same change in vessel pressure. This is experimentally and operationally advantageous, as it allows finer control of vessel gas pressure. Divertor fuelling on JET results in toroidally symmetric gas pressure in contrast to mid-plane fuelling where vessel gas pressure is larger in the toroidal location close to the injecting valve. The toroidally symmetric gas pressure distribution means that divertor fuelled breakdowns are easier to interpret which is experimentally and operationally advantageous.

Dedicated Ohmic breakdown references were performed using the same setup as for the IC assisted breakdowns only with the IC power turned off.

Since JET began operating with the ITER-like Be/W wall (JET-ILW), plasma initiation has been robust with failed

plasma initiations being rare [15, 16]. This is when operating with breakdown $E_{loop} \approx 0.9 \text{ Vm}^{-1}$ and $B_t \geq 2.3 \text{ T}$ to ensure sufficiently long connection lengths. To study an ITER relevant regime where E_{loop} and connection lengths may be low enough that plasma initiation becomes marginal, these studies were performed with $E_{loop} \lesssim 0.33 \text{ Vm}^{-1}$ and $B_t \approx 1.7 \text{ T}$. JET plasma initiation had not previously been achieved in such conditions.

Diagnosis follows the approach used in previous JET breakdown studies [16]. The loop electric field is inferred from the central solenoid (P1 coil) voltage, V_{P1} . The P1 coil has $N_T = 710$ turns, so $V_{P1} = 2\pi R_0 N_T E_{loop}$, where $R_0 = 2.96 \text{ m}$ is the JET geometric radius. In-vessel neutral gas pressure is measured with Penning gauges [17, 18]. The line integrated density is measured with the JET far-infrared interferometer using a vertical line of sight passing through the centre of vessel with a time resolution of $10 \mu\text{s}$ [19, 20]. Bremsstrahlung and D Balmer- α emission is measured by a visible spectroscopy system with multiple lines of sight and 1 ms time resolution [21]. Z-effective is inferred from Bremsstrahlung radiation. The JET VUV emission spectroscopy system is used to measure line radiation from impurities, including Be III, C III, C IV, O VI, Ne VII, Ne VIII, Ne IX, Ar XVI, Fe XXIII, Ni XVIII and W (multiple lines) [22].

3. Criteria for successful plasma initiation

3.1. Overview of the JET IC assisted breakdown results

Plasma initiation with IC assisted breakdown has been successfully established in the regime of interest for ITER, $E_{loop} < 0.33 \text{ Vm}^{-1}$, for a range of fields $B_t = 1.7 - 2.3 \text{ T}$.




Figure 2. Time trace of plasma parameters for an IC assisted breakdown (red, #100624) and an Ohmic breakdown (blue, #100636) with D_2 fuelling. (a) Plasma current; (b) coupled RF power; (c) P1 coil voltage; (d) the line average density; (e) in-vessel gas pressure in octant 1; (f) in-vessel gas pressure in octant 5; (g) D - α emission; and (h) injected gas.

Figure 2 shows a typical discharge (red, #100624) compared with an Ohmic breakdown (blue, #100636) at matched $E_{loop} \lesssim 0.33 \text{ Vm}^{-1}$ and $B_t = 1.7 \text{ T}$. In the period before the main breakdown phase, a low density, $n_e \leq 5 \times 10^{18} \text{ m}^{-3}$, plasma is produced in the vacuum vessel by powering the IC antennas. After an initial increase of the torus gas pressure due to gas fuelling in vacuum, the pressure falls at the onset of the IC discharge due to wall pumping. This process eventually saturates as shown by the gradual pressure increase from $\approx 0.25 \text{ s}$. The, so-called, ‘pre-ionisation’ plasma is maintained until the start of the main breakdown phase. The torus pressure at breakdown can be tuned by the gas fuelling rate and the launched IC power. The plasma density rise rate through the breakdown and plasma burn through phases is much higher than for the Ohmic reference. The following analysis will look

more carefully into successful and unsuccessful plasma initiation attempts for both Ohmic only and IC assisted scenarios. It is important to note that most of pulses achieved breakdown while many failed in the burn through phase. Hence, a successful plasma initiation is hereafter defined by a successful completion of the plasma burn through phase. Consistent with previous studies, the time point at which the JET plasma current reaches 100 kA is used to define the loop electric field and neutral gas pressure of the plasma breakdown [16].

Figure 3 shows the full set of IC assisted breakdown discharges in this study. A range of breakdown pressures and toroidal (loop) electric fields were attempted with D_2 fuelling at three different toroidal magnetic fields, $B_t = 1.7, 2.0,$ and 2.3 T . A range of breakdown pressures and toroidal (loop) electric fields were also attempted with




Figure 3. Toroidal (loop) electric field versus prefill gas pressure, both at the time of breakdown, for all attempted IC assisted breakdown discharges in this study with $B_T = 1.7$ T (red squares), $B_T = 2.0$ T (blue squares), and $B_T = 2.3$ T (black squares). H_2 fuelled discharges are marked with a blue ‘*’ symbol; discharges are D_2 fuelled otherwise. Failed plasma initiations are marked with an ‘x’. Dashed grey contours denote contours of constant λ_i using the breakdown criteria of equation (1). Dashed vertical lines show the operational range for successful plasma initiation at $B_T = 1.7$ T (red) and $B_T = 2.0$ T (blue). Dashed black line shows the minimum $E_{loop} = 0.22$ Vm^{-1} at which plasma initiation was achieved.

H_2 fuelling at $B_T = 2.3$ T. The minimum E_{loop} for plasma initiation is 0.22 Vm^{-1} for both $B_T = 1.7$ T and $B_T = 2.3$ T. A full pressure scan was conducted at $B_T = 1.7$ T with $E_{loop} \leq 0.33$ Vm^{-1} with the pressure range for successful plasma initiation identified as $0.5 - 2.4$ mPa. The minimum pressure for successful IC assisted initiation appears to be independent of toroidal magnetic field (≈ 0.5 mPa), but IC assisted initiation was still successful for the highest pressure attempted at $B_T = 2.0$ T (≈ 5 mPa). It is preliminarily concluded that the operational space of pressure is larger for higher B_T , in line with the fact that connection length scales linearly with field. H_2 breakdowns appear to show the same trends as for D_2 ones, although the dataset of H_2 breakdowns is more limited.

3.2. Comparison of IC assisted and Ohmic initiation

To understand whether IC assistance improves the robustness of plasma initiation, comparison pulses with Ohmic breakdown only were selected from previous JET-ILW pulses. There have been over 20 000 attempted Ohmic breakdowns in the JET-ILW. As it is the more robust approach, most attempted breakdowns in JET are with a toroidal voltage induced by a current interruption in the primary coil (referred to as ‘mode D’ breakdown in JET). These breakdowns typically have $0.7 < E_{loop} < 1.0$ Vm^{-1} and are not comparable to the IC assisted breakdowns here. The Ohmic pulses selected for this study have the primary coil voltage under direct control (referred to as ‘mode B’ breakdown in JET), as was the case for the IC assisted ones. These Ohmic breakdowns have similar $E_{loop} \leq 0.5$ Vm^{-1} to the IC assisted ones. Amongst these pulses, most have the prefill gas injected immediately before the breakdown time and so the torus pressure is highly asymmetrical. Such pulses are excluded from the dataset here and only pulses with prefill gas 0.5 s earlier than breakdown time, where the torus pressure is equalised and

suitable for data analysis, are selected. The resulting dataset comprises 77 JET-ILW Ohmic breakdown pulses suitable for comparison with the IC assisted breakdown pulses introduced in section 3.1.

Figure 4 shows the operational range of the reference Ohmic only breakdowns. Figure 4 includes both succeeded and failed pulses. Many of the attempted breakdowns are part of a previous study to achieve ITER-like ($E_{loop} \leq 0.33$ Vm^{-1}) breakdown. In that study, breakdown could only be achieved at $B_T = 2.8 - 3.0$ T which is associated with longer connection lengths. The success rate of Ohmic only breakdowns with $B_T \leq 2.3$ T for $E_{loop} \leq 0.5$ Vm^{-1} is much lower than that of the IC assisted breakdowns and the achieved operational pressure range is narrow, $\approx 2.5 - 4.0$ mPa. The majority of successful Ohmic breakdowns at higher $B_T = 2.8 - 3.0$ T also fall within a similar operational pressure range $\approx 2.0 - 4.5$ mPa.

The successful IC assisted breakdowns and Ohmic only breakdowns are shown in figures 5(a) and (b) respectively. For the same B_T , the operational pressure range of the IC assisted breakdowns is wider than for the Ohmic only breakdowns and the minimum E_{loop} is lower for the IC assisted breakdowns. The minimum achieved E_{loop} for plasma initiation is 0.25 Vm^{-1} . The majority of the $B_T = 2.0$ T Ohmic breakdowns were from a set of experiments where the E_{loop} and prefill pressure were optimised to ensure robust breakdown and their operational range for successful breakdown was not explored.

Although the Ohmic breakdown references have been selected so as to best match the IC assisted breakdowns presented in section 3.1, they still represent breakdowns which were often performed many years before, potentially under different machine conditions and with different prefill gas delivery. The previous Ohmic breakdowns also contained relatively few discharges with connection lengths comparable to the IC assisted breakdown discharges, that is comparable B_T . As it




Figure 4. Toroidal (loop) electric field versus prefill gas pressure, both at the time of breakdown, for all attempted IC assisted breakdown discharges in this study with $B_t = 1.7$ T (red squares), $B_t = 2.0$ T (blue squares), $B_t = 2.3$ T (black squares), and $B_t = 2.8 - 3.0$ T (green squares). Failed plasma initiations are marked with an ‘x’. Dashed grey contours denote contours of constant λ_i using the breakdown criteria of equation (1).




Figure 5. Operational range of IC assisted initiation vs Ohmic only ones. Toroidal (loop) electric field versus prefill gas pressure, both at the time of breakdown, for all successful (a) IC assisted breakdown discharges and (b) Ohmic only breakdown references in this study with $B_t = 1.7$ T (red squares), $B_t = 2.0$ T (blue squares), $B_t = 2.3$ T (black squares), and $B_t = 2.8 - 3.0$ T (green squares). Dashed grey contours denote contours of constant λ_i using the breakdown criteria of equation (1).

was not the focus of the experiments in which many of the previous Ohmic breakdowns occurred, the operational range for successful breakdown was often not explored and so cannot clearly be deduced. For these reasons, as part of the current experiment, Ohmic only breakdowns with D_2 fuelling at $E_{loop} \leq 0.33 \text{ Vm}^{-1}$ and $B_t = 1.7$ T were performed as dedicated references for IC assisted pulses with otherwise identical settings. Some of these were also successful, representing the first Ohmic breakdowns established at ITER-PFPO-like E_{loop} and B_t in JET. As for the IC assisted breakdowns, a full (seven-point) pressure scan was completed at $B_t = 1.7$ T,

figure 6(a). The pressure range for successful plasma initiation with Ohmic breakdown at $B_t = 1.7$ T was observed to be 2.5 – 4.0 mPa, consistent with that of the wider Ohmic breakdown dataset as noted earlier. Hence, IC assisted breakdown enables plasma initiation with five times lower gas prefill pressure and a much wider range (0.5 – 2.4 mPa). This gives access to the 1 mPa prefill pressure that is proposed for ITER [4]. The amount of injected prefill gas for successful plasma initiation with IC assisted breakdown (7.7 – 10.9 kPa l) is greater than for Ohmic breakdown (4.3 – 4.4 kPa l) with a considerably larger range, figure 6(b). As the amount of injected prefill gas




Figure 6. E_{loop} against (a) torus pressure immediately prior to breakdown; and (b) total injected gas prior to breakdown for Ohmic only (orange squares) and IC assisted (black diamonds) breakdowns in JET with D_2 fuelling at $B_t = 1.7$ T. Failed plasma initiations are marked with an ‘x’.




Figure 7. E_{loop} against (a) torus pressure immediately prior to breakdown; and (b) total injected gas prior to breakdown for IC assisted breakdowns in JET at $B_t = 1.7$ T with D_2 fuelling. Discharges with liquid N_2 cooled pumped divertor (pump speed ≈ 5 $m^3 s^{-1}$) marked by blue open squares; other discharges have liquid He cooled pumped divertor (pump speed ≈ 150 $m^3 s^{-1}$). Failed plasma initiations are marked with an ‘x’.

is the controlled parameter experimentally, Ohmic breakdown at $E_{loop} \leq 0.33$ Vm^{-1} and $B_t = 1.7$ T requires careful gas control, and is presumably sensitive to vessel condition, whilst IC assisted breakdown is more robust.

3.3. The impact of pumping

The impact of divertor cryo-pump condition was explored by comparing breakdowns attempted with the cryo-pump cooled by liquid N_2 and liquid He, which affect the pumping efficiency of hydrogen. For both H_2 and D_2 gas fuelling the JET divertor cryo-pump is found to pump at ≈ 150 $m^3 s^{-1}$ when liquid He cooled and at ≈ 5 $m^3 s^{-1}$ when liquid N_2 cooled. At both temperatures, scans of pre-fill gas pressure were performed with IC assisted breakdown with $E_{loop} < 0.33$ Vm^{-1} at $B_t = 1.7$ T. A pre-fill gas pressure scan was also performed with the cryo-pump cooled by liquid N_2 for

Ohmic breakdown with the same E_{loop} and B_t . The impact of this on the breakdown studies can be seen by comparing the IC assisted D breakdown discharges at $B_t = 1.7$ T with the two divertor cryo-pump coolants, figure 7. For both pumping conditions, a similar range of gas prefill pressure, $\approx 0.6 - 3.0$ mPa, is observed for successful IC assisted breakdowns, figure 7(a). The range of pre-fill gas fuelling that is required to achieve these pressures is also similar with the two cryo-pump coolants, $\approx 75 - 110$ mbar l, figure 7(b). Thus, for IC assisted breakdown, cryo-pump condition does not seem to obviously affect the breakdown pressure or the total injected pre-fill gas.

3.4. The role of IC wave injection in breakdown

Comparing IC assisted with Ohmic breakdown with the cryo-pump at liquid N_2 temperature, clearly the breakdown




Figure 8. Pressure at which breakdown is achieved versus the total injected gas prior to breakdown for Ohmic only (orange squares) and IC assisted (black diamonds) breakdowns in JET with D_2 fuelling. Discharges with liquid N_2 cooled pumped divertor (pump speed $\approx 5 \text{ m}^3 \text{ s}^{-1}$) marked by blue open squares; other discharges have liquid He cooled pumped divertor (pump speed $\approx 150 \text{ m}^3 \text{ s}^{-1}$). Failed plasma initiations are marked with an ‘x’.

pressure and the total injected pre-fill gas ranges differ significantly, figure 8. The effective pumping speed, S , can be calculated from the expression for the time evolution of the gas prefill pressure $p(t)$

$$V \frac{dp(t)}{dt} = -S[p(t) - p_L] + F(t), \quad (2)$$

where V is the total pumped torus volume, $\approx 180 \text{ m}^3$; p_L is the stable torus pressure, $\approx 0.03 \text{ mPa}$ for the N_2 cooled pump divertor; and $F(t)$ is the time dependent gas injection rate. The total pumping speed is found to be $\approx 20 \text{ m}^3 \text{ s}^{-1}$ for Ohmic breakdown pulses and $\approx 1000 \text{ m}^3 \text{ s}^{-1}$ for the IC assisted breakdown pulses. The applied IC acts as a pump which greatly increases the amount of gas consumed by breakdown. As outlined in [23], IC power applied to breakdown the plasma creates additional pumping through its impact on normal neutral particle processes (fluxes to the wall and disassociation of molecular hydrogen or deuterium) and through the production of fast neutrals by charge exchange between protons or deuterons accelerated in the IC resonant layer and the background neutral gas.

There is no strong trend across the dataset of a correlation between IC coupled power and successful plasma initiation. Some pulses with poor coupling (lower ICWC n_e) during IC pre-ionisation phase succeeded in plasma initiation, while some failed with well coupled power. There was no strong trend between the IC preionisation plasma density and breakdown either. Figure 9 illustrates this for a D_2 breakdown assisted with 33 MHz IC. Discharge #100416 (blue trace) is a successful $E_{\text{loop}} < 0.33 \text{ Vm}^{-1}$, $B_t = 1.7 \text{ T}$ IC assisted discharge. Discharge #100408 (red trace) with similar loop voltage failed in plasma initiation. Coupled IC power is higher for this discharge and is associated with considerably

(≈ 2 times) higher preionisation electron density. Despite this, the current fails to take off.

As outlined in section 3.2, Ohmic only and IC assisted plasma initiations differ significantly. Given that Ohmic only plasma initiations are equivalent to IC assisted plasma initiations with IC coupled and applied power of zero, clearly the amount of IC couple power does affect successful plasma initiation. The lack of correlation in the experiments likely results from the limited dataset and the interplay between plasma formation and IC power coupling. As discussed in section 1, the injected IC power and all other setting of the IC system are identical for all IC assisted breakdowns in this study. Hence, the coupled power depends only on the plasma conditions, including the plasma density.

Across all the IC assisted discharges, the IC preionisation plasma has low density, $n_e < 5 \times 10^{18} \text{ m}^{-3}$, and there is no correlation observed between IC plasma density and density at the end of the burn through. The time when $I_p = 100 \text{ kA}$ may be taken as the approximate end of the burn through. At this time the IC assisted breakdown pulses have higher electron density than Ohmic breakdowns, even at similar prefill gas pressures, figure 10(a). Even though the total injected gas is lower in Ohmic only breakdowns than IC assisted ones, the density at breakdown is similar, figure 10(b).

3.5. The impact of impurities

Compared with Ohmic only assisted breakdown, IC assisted breakdown can initiate plasma in the presence of higher levels of impurities, such as Ne. This was demonstrated with a study of breakdown with D_2 fuelling in the presence of high in-vessel Ne concentrations. Ohmic breakdown was first attempted at $E_{\text{loop}} \lesssim 0.33 \text{ Vm}^{-1}$. Despite three consecutive attempts




Figure 9. Time trace of plasma parameters for a successful (blue, #100416) and a failed (red, #100408) plasma initiation with IC assisted breakdown and D₂ fuelling. (a) Plasma current; (b) injected RF power; (c) coupled RF power; (d) P1 coil voltage; (e) line average density; (f) in-vessel gas pressure in octant 1; (g) in-vessel gas pressure in octant 5; and (h) D- α emission.




Figure 10. Electron density, at the time in the breakdown where $I_p = 100$ kA, against (a) torus pressure at the same time; and (b) total injected gas prior to breakdown for Ohmic and IC assisted breakdowns in JET.




Figure 11. Time trace of plasma parameters for an unsuccessful Ohmic breakdown (red, #100401), the immediately following successful IC assisted breakdown (magenta, #100404) both are D_2 fuelled with high intrinsic impurity levels. The reference successful Ohmic breakdown (blue, #98343) is also shown. (a) Plasma current; (b) coupled RF power; (c) P1 coil voltage; (d) in-vessel gas pressure in octant 1; (e) in-vessel gas pressure in octant 1; (f) $D\text{-}\alpha$ emission; and (g) injected gas.

at different pressures around the optimal value, Ohmic breakdown was unsuccessful. Figure 11 shows one of the unsuccessful Ohmic only breakdowns (#100401, red) which was based on a reference successful Ohmic only breakdown (#98343, blue). Despite similar prefill fuelling, prefill gas pressure, and loop electric field to the reference at $t = 0.45$ s, the breakdown for #100401 is clearly un-sustained. IC assisted initiation #100404 was then attempted and was successful straight away. Figure 12 shows plasma parameters for the successful IC assisted breakdown discharge (#100404, red) against that of the previously successful Ohmic pulse (#98343, blue). The Ohmic reference has line radiation from Ne lines which are essentially at or below the background noise. #100404 has much higher neon levels, but these do not prevent plasma initiation. As no wall cleaning was attempted after the previous attempts (#100401-#100403), it is safe to assume that they

would have had similar, high neon levels. The high neon content comes from the previous session which actively injected neon for experimental purposes. The failure of the Ohmic only breakdown and the success of the IC assisted breakdown for the same high Ne level vessel conditions shows that IC assisted breakdowns can tolerate higher impurity levels than Ohmic only ones in JET with the ITER-like wall.

4. Breakdown and burn through evolution

4.1. The parametric dependency of the plasma current rise rate

The plasma current rise rate after breakdown is defined, for these studies, as the average of dI_p/dt over the period between $I_p = 100$ kA and $I_p = 200$ kA. This is always before I_p is in




Figure 12. Time trace of plasma parameters for the D₂ fuelled, IC breakdown discharge with high levels of Ne impurity of figure 11 (magenta, #100404) and the D₂ fuelled, Ohmic only breakdown reference discharge with low levels of Ne impurity of figure 11 (blue, #98343). (a) Plasma current; (b) coupled RF power; (c) P1 coil voltage; (d) Ne VII line emission intensity; (e) Ne VIII line emission intensity; and (f) Ne IX line emission intensity.

feedback control and is freely evolving. For both IC assisted and Ohmic breakdown, the plasma current rise rate after breakdown inversely correlates with the electron density at breakdown and positively correlates with E_{loop} . This can be seen in figure 13 where breakdown n_e/E_{loop} is well, inversely correlated with the I_p rise rate. Higher E_{loop} drives faster I_p rise rate. Higher n_e is associated with lower T_e for the same plasma energy, which results in higher resistance and so lower I_p rise rate. For Ohmic breakdown, I_p rises much faster, at similar pressure, than for IC assisted breakdowns. Comparing the breakdowns with the cryo-pump cooled by liquid N₂ and liquid He, there is no evidence of the divertor condition affecting the I_p rise rate.

Although Ohmic breakdown happens at higher vessel pressure, n_e is lower compared with IC assisted breakdown, as the examples (#100624 vs #100636) shown in figure 2. I_p rises faster for higher B_t for the same breakdown prefill gas pressure, figure 14(a). This is consistent with the observation that IC assisted breakdown pulses have higher electron density than Ohmic breakdowns at similar prefill gas

pressures, section 3.4. There is no notable isotope effect. There is a strong, negative correlation between the I_p rise rate and n_e/E_{loop} across the whole dataset, figure 14(b).

4.2. The impact of IC assisted breakdown on plasma impurities

IC heating on JET has been observed to be associated with impurity production [24–29]. The impurities concerned include Ni and Be, resulting from interactions with the Ni components of the IC antennas or the Be limiters around them, as well as other low-Z and high-Z impurities. For IC assisted breakdown pulses, no sign of increased impurities level in current ramp-up or later phases. Figure 15 shows an example IC assisted breakdown discharge and its Ohmic only breakdown reference. The lines shown cover the impurities commonly found in JET discharges which can contribute significantly to Bremsstrahlung and total plasma radiation. Plasma initiation for both discharges is successful. Line radiation from low




Figure 13. Plasma current rise rate, averaged over the period between $I_p = 100$ kA and $I_p = 200$ kA versus (a) toroidal electric field; (b) vessel pressure; and (c) vessel pressure normalised to the toroidal electric field for a series of Ohmic (orange diamonds) and IC assisted (black diamonds) JET breakdowns with $B_t = 1.7$ T and D_2 fuelling. Discharges with liquid N_2 cooled pumped divertor (pump speed ≈ 5 m³ s⁻¹) marked by blue open squares; other discharges have liquid He cooled pumped divertor (pump speed ≈ 150 m³ s⁻¹).




Figure 14. Plasma current rise rate, averaged over the period between $I_p = 100$ kA and $I_p = 200$ kA, versus (a) vessel pressure normalised to toroidal electric field; and (b) electron density normalised to toroidal electric field for IC assisted JET breakdowns with $B_t = 1.7$ T (black diamonds), $B_t = 2.0$ T (blue diamonds), and $B_t = 2.3$ T (orange diamonds). H_2 fuelled discharges are marked with a blue ‘*’ symbol; discharges are D_2 fuelled otherwise.




Figure 15. Time trace of Z-effective and impurities commonly present in JET discharges for a successful IC assisted breakdown (red, #100628) and a successful Ohmic breakdown (blue, #100636). (a) Line average Z-effective and the line emission intensity of (b) carbon IV (c) iron XXIII, (d) nickel XVIII, (e) oxygen VI, (f) carbon III, (g) beryllium IV, (h) argon XVI, (i) neon VIII, and (j) tungsten.

Z and high Z impurities and the Z-effective for the two discharges is similar throughout plasma burn through and later flat-top phase. There is no evidence of increased Ni or Be impurities.

5. Summary and implication of the results

For the first time on JET, a series of IC wave assisted breakdown experiments have been performed to provide a physics basis for validating models for testing and optimising plasma initiation with IC assisted breakdown for ITER. RF operation and protection, fuelling time and location, and the range of breakdown pressure and E_{loop} were studied. The IC assisted breakdowns were compared with Ohmic breakdowns performed under similar conditions from previous experiments as well as dedicated Ohmic breakdowns performed as part of the experiment in conditions as closely matched as possible to the IC assisted breakdowns.

For the first time, both IC assisted and Ohmic breakdown were achieved in D for the regime planned for the first pre-fusion operation (PFPO-1) phase of ITER, $E_{\text{loop}} \lesssim 0.33 \text{ Vm}^{-1}$ with $B_t = 1.7 \text{ T}$ and where EC breakdown assistance with 170 GHz waves would not work. All discharges, IC assisted or

otherwise, achieved breakdown; successful plasma initiation was determined by the success of the subsequent plasma burn through phase.

In the studies, plasma initiation with IC assisted breakdown was significantly more robust than Ohmic breakdowns with the same E_{loop} and B_t . For the IC assisted breakdowns at the lowest fields explored, $B_t = 1.7 \text{ T}$ and $E_{\text{loop}} \lesssim 0.33 \text{ Vm}^{-1}$, breakdown is achieved at lower pressures for a wider range and with significantly higher amounts of injected gas for a wider range than Ohmic only references. Plasma initiation with IC assisted breakdowns was also achieved with higher impurity content than for Ohmic breakdown references. To get the same prefill gas pressure, IC breakdowns required considerably higher injected prefill gas than Ohmic breakdowns showing that the IC acts as a pump. Thus, IC assisted breakdown enables plasma initiation with a higher level and wider range of injected plasma prefill gas. As the injected prefill gas is the controlled parameter, this significantly improves the robustness of plasma initiation operationally.

Divertor fuelling on JET provides a more symmetric torus pressure than the more common mid-plane fuelling, enabling easier control and analysis of breakdowns. It is recommended that divertor fuelling is used for future breakdown studies and that the toroidal asymmetry is considered when validating breakdown models on mid-plane fuelled discharges. No

obvious influence of cryo-pump condition on breakdown pressure range was observed.

Turning to the evolution of the breakdown and plasma burn through, the I_p rise rate is well (negatively) correlated with the n_e/E_{loop} across the full dataset which includes Ohmic and IC assisted breakdowns and a wide range of B_r , bulk isotope species, and pumped divertor temperatures. There is no evidence of increased impurity level for IC assisted breakdown in the current ramp-up and later phases.

As successful burn through determines the success of plasma initiation, combining IC pre-ionisation with IC assisted burn through and ramp-up phases may further extend the operational range. Such a recipe on JET requires the use of different antennas one or more tuned for the pre-ionisation plasma and one or more for the later phases. This is intended to be the subject of future experiments.

Ohmic plasma initiation on JET-ILW has previously been shown to be consistent with the DYON plasma burn through simulator based on a parametrised confinement time and impurity fluxes based on a wall-sputtering model [30, 31]. The data from all the studies presented here will be provided as a basis for model validation for plasma initiation on ITER and other devices. However, the demonstration in the ITER relevant regime that IC assistance extends the access to breakdown without any evidence for enhanced impurities already gives significant confidence that its use on ITER will also be important for assisting breakdown in the pre-fusion operation phase.

Data availability statement

All data that support the findings of this study are included within the article (and any supplementary files).

Acknowledgments

This work has been carried out within the framework of the EUROfusion Consortium, funded by the European Union via the Euratom Research and Training Programme (Grant Agreement No. 101052200—EUROfusion) and from the EPSRC [Grant Number EP/W006839/1]. Views and opinions expressed are however those of the authors only and do not necessarily reflect those of the European Union or the European Commission. The Swiss contribution to this work has been funded by the Swiss State Secretariat for Education, Research and Innovation (SERI). Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union, the European Commission or SERI. Neither the European Union nor the European Commission nor SERI can be held responsible for them. The views and opinions expressed herein do not necessarily reflect those of the ITER Organization.

ORCID iDs

H J Sun  <https://orcid.org/0000-0003-0880-0013>

T Wauters  <https://orcid.org/0000-0002-2941-7817>

P C De Vries  <https://orcid.org/0000-0001-7304-5486>

B Labit  <https://orcid.org/0000-0002-0751-8182>

References

- [1] Kim H *et al* 2023 On the Path to Burning Plasma Operation (Nuclear Fusion special Issue by ITPA-IOS): Section 2. Plasma Initiation in preparation for Nucl. Fusion
- [2] Lloyd B 1991 Nucl. Fusion **31** 2031
- [3] Gribov Y, Humphreys D, Kajiwara K, Lazarus E A, Lister J B, Ozeki T, Portone A, Shimada M, Sips A C C and Wesley J C 2007 Nucl. Fusion **47** S385
- [4] de Vries P C and Gribov Y 2019 Nucl. Fusion **59** 096043
- [5] Kajiwara K, Ikeda Y, Seki M, Moriyama S, Oikawa T, Fujii T and Team J-6 2005 Nucl. Fusion **45** 694
- [6] Bae Y 2009 Nucl. Fusion **49** 022001
- [7] Stoeber J *et al* 2011 Nucl. Fusion **51** 083031
- [8] Sips A, Giruzzi G, Ide S, Kessel C, Luce T C, Snipes J A and Stober J K 2015 Phys. Plasmas **22** 021804
- [9] Sinha J *et al* 2022 Nucl. Fusion **62** 066013
- [10] Ricci D, Stober J, Dux R, Figini L, Wauters T, Lerche E and Granucci G 2023 EPJ Web Conf. **277** 02001
- [11] Farina D 2018 Nucl. Fusion **58** 066012
- [12] Lyssoivan A *et al* 2012 Plasma Phys. Control. Fusion **54** 074014
- [13] Luo J R *et al* 2000 Low Loop Voltage Start-up in HT-7 Tokamak with ICRF IAEA Fusion Energy Conf. (Sorrento, Italy, 4-10 October) (available at: www-pub.iaea.org/MTCD/publications/PDF/CSP_008C/HTML/node130.htm)
- [14] Maviglia F, Albanese R, Alonso A and Lomas P J 2011 Fusion Eng. Des. **86** 675
- [15] Romanelli F *et al* 2013 Nucl. Fusion **53** 104002
- [16] de Vries P *et al* 2013 Nucl. Fusion **53** 053003
- [17] Hillis D, Morgan P D, Ehrenberg J K, Groth M, Stamp M F, von Hellermann M and Kumar V 1999 Rev. Sci. Instrum. **70** 359
- [18] Kruezi U, Sergienko G, Morgan P D, Matthews G F, Brezinsek S and Vartanian S 2012 Rev. Sci. Instrum. **83** 10D728
- [19] Braithwaite G, Gottardi N, Magyar G, O'Rourke J, Ryan J and Véron D 1989 Rev. Sci. Instrum. **60** 2825
- [20] Boboc A, Gil C, Pastor P, Spuig P, Edlington T and Dorling S 2012 Upgrade of the JET far infrared interferometer diagnostic Rev. Sci. Instrum. **83** 10E341
- [21] Morgan P, Behringer K H, Carolan P G, Forrest M J, Peacock N J and Stamp M F 1985 Rev. Sci. Instrum. **56** 862
- [22] Czarnecka A, Zastrow K-D, Rzadkiewicz J, Coffey I H, Lawson K D and O'Mullane M G 2011 Plasma Phys. Control. Fusion **53** 035009
- [23] Douai D *et al* 2015 J. Nucl. Mater. **463** 150–6
- [24] Bures M, Jacquinet J, Lawson K, Stamp M, Summers H P, D'Ippolito D A and Myra J R 1991 Plasma Phys. Control. Fusion **33** 937
- [25] D'Ippolito D, Myra J R, Bures M, Stamp M and Jacquinet J 1990 Fusion Eng. Des. **12** 209
- [26] D'Ippolito D, Myra J R, Bures M and Jacquinet J 1991 Plasma Phys. Control. Fusion **33** 607
- [27] Bures M, Jacquinet J J, Stamp M F, Summers D D R, Start D F H, Wade T, D'Ippolito D A and Myra J R 1992 Nucl. Fusion **32** 1139
- [28] Perkins F 1989 Nucl. Fusion **29** 583
- [29] Czarnecka A *et al* 2012 Plasma Phys. Control. Fusion **54** 074013
- [30] Kim H, Fundamenski W and Sips A C C 2012 Nucl. Fusion **52** 103016
- [31] Kim H and Sips A C C 2013 Nucl. Fusion **53** 083024